

屋内照明器具特性

品番 (品名)	XAD3 1 0 1 K				
光源	LLD3 0 0 0 CU1 x1		7 9 5 . 0 l m		
管理番号	K0178936 (0) DR 1				
B Z 分類	BZ4 / 0 . 7 / BZ3				

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		68 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X 0 . 0 1)																				Z C M
保守率	良	0 . 6 7	0 . 6	4 2	3 4	2 9	2 6	4 1	3 4	2 9	2 6	3 9	3 3	2 9	2 6	3 8	3 2	2 9	2 6	2 4	
	中	0 . 6 3	0 . 8	4 9	4 2	3 7	3 4	4 8	4 2	3 7	3 4	4 6	4 1	3 7	3 4	4 5	4 0	3 6	3 3	3 2	
	否	0 . 5 6	1 . 0	5 3	4 7	4 3	3 9	5 3	4 7	4 3	3 9	5 1	4 6	4 2	3 9	4 9	4 5	4 2	3 9	3 8	
	下方投影面積		c m ²	1 . 2 5	5 7	5 2	4 8	4 5	5 6	5 1	4 8	4 5	5 5	5 0	4 7	4 4	5 3	4 9	4 6	4 4	4 3
等価発光面積		c m ²	1 . 5	6 0	5 5	5 1	4 8	5 9	5 5	5 1	4 8	5 7	5 3	5 0	4 8	5 6	5 2	5 0	4 7	4 6	
		c m ²	2 . 0	6 4	6 0	5 6	5 4	6 3	5 9	5 6	5 3	6 1	5 8	5 5	5 3	5 9	5 7	5 4	5 2	5 1	
取付高さ	器具間隔最大限		2 . 5	6 6	6 2	6 0	5 7	6 5	6 2	5 9	5 7	6 3	6 0	5 8	5 6	6 1	5 9	5 7	5 6	5 4	
	横方向 (A)	縦方向 (B)	3 . 0	6 7	6 4	6 2	6 0	6 6	6 3	6 1	5 9	6 4	6 2	6 0	5 8	6 3	6 1	5 9	5 8	5 6	
H m	1 . 2 3 H m	1 . 2 3 H m	4 . 0	6 9	6 6	6 4	6 3	6 8	6 6	6 4	6 2	6 6	6 4	6 3	6 1	6 4	6 3	6 2	6 1	5 9	
			5 . 0	7 0	6 8	6 6	6 5	6 9	6 7	6 6	6 4	6 7	6 6	6 4	6 3	6 5	6 4	6 3	6 2	6 1	
			7 . 0	7 1	6 9	6 8	6 7	7 0	6 9	6 8	6 7	6 8	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 2	
			1 0 . 0	7 2	7 1	7 0	6 9	7 1	7 0	6 9	6 8	6 9	6 8	6 8	6 7	6 8	6 7	6 6	6 6	6 4	

