

屋内照明器具特性

品番 (品名)	XLGE5103										
光源	LLD2000NCE1 ×1 531.0 lm										
管理番号	K0181597(0)DR1										
BZ分類	BZ5/0.7/BZ4										

器具効率	72%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	72%	室指数	照明率 (×0.01) ZCM																	
保守率	良 0.63	0.6	41	33	27	23	40	32	27	23	39	31	27	23	37	31	26	23	22	
	中 0.6	0.8	48	40	35	31	47	40	35	31	45	39	34	31	44	38	34	30	29	
	否 0.56	1.0	53	46	40	36	52	45	40	36	50	44	39	36	48	43	39	36	34	
		1.25	57	51	46	42	56	50	45	41	54	49	45	41	52	48	44	41	39	
下方投影面積	cm ²	1.5	60	54	49	46	59	54	49	45	57	52	48	45	55	51	47	45	43	
		2.0	64	59	55	52	63	58	55	51	61	57	54	51	59	56	53	50	48	
取付高さ	器具間隔最大限		2.5	67	62	59	56	66	62	58	55	64	60	57	55	62	59	56	54	52
	横方向 (A)	縦方向 (B)	3.0	68	65	61	59	67	64	61	58	65	62	60	57	63	61	59	57	55
H _m	1.22H _m	1.22H _m	4.0	71	68	65	63	70	67	64	62	68	65	63	61	66	64	62	60	58
			5.0	72	70	67	65	71	69	67	65	69	67	65	64	67	66	64	63	61
			7.0	73	72	70	68	73	71	69	68	71	69	68	67	69	68	67	66	64
			10.0	75	73	72	71	74	72	71	70	72	71	70	69	70	69	69	68	66

