

# 屋内照明器具特性

品番 (品名)	LGB81888														
光源	LED3500_70_1015 x1 1015.0 lm														
管理番号	K0174241(0)DR1														
BZ分類	BZ7														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	31% 69%	室指数	照明率 ( X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	47	34	26	20	44	33	25	20	39	29	22	18	34	26	20	16	12		
		0.8	56	43	35	28	52	41	33	27	46	36	30	25	40	32	26	22	17		
		1.0	62	50	41	34	58	47	39	33	51	42	35	30	44	37	31	27	21		
		1.25	67	56	47	41	63	53	45	39	55	47	41	35	48	42	36	32	25		
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	72	61	53	46	67	58	50	44	59	51	45	40	51	45	40	36	28		
		2.0	77	68	60	54	73	64	57	51	64	57	51	47	56	51	46	42	34		
取付 高さ	器具間隔最大限		2.5	81	73	66	60	76	69	62	57	67	61	56	52	59	54	50	46	37	
	横方向 (A)	縦方向 (B)	3.0	84	76	70	64	79	72	66	61	70	65	60	55	62	57	53	50	41	
1.5m	2.12 m	1.95 m	4.0	87	81	75	71	82	77	72	67	73	69	65	61	65	61	58	55	45	
2	2.81	2.56	5.0	90	84	79	75	85	80	76	71	76	72	68	65	67	64	61	58	48	
2.5	3.52	3.18	7.0	92	88	84	81	88	84	80	77	79	75	72	70	70	67	65	63	52	
3	4.21	3.8	10.0	95	91	88	85	90	87	84	82	81	78	76	74	72	70	68	67	56	

