

屋内照明器具特性

品番 (品名)	LGC21182														
光源	LED4000_70_2900 x1 2900.0 1m														
管理番号	K0179197(0)DB1														
BZ分類	BZ5/0.7/BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)															ZCM		
保守率	良	0.67	0.6	5.8	4.6	3.8	3.3	5.7	4.5	3.8	3.3	5.4	4.4	3.7	3.3	5.2	4.3	3.7	3.3	3.1
	中	0.63	0.8	6.8	5.7	4.9	4.4	6.7	5.6	4.9	4.4	6.4	5.5	4.8	4.3	6.1	5.4	4.8	4.3	4.1
	否	0.56	1.0	7.5	6.5	5.7	5.2	7.3	6.4	5.7	5.1	7.0	6.2	5.6	5.1	6.8	6.1	5.5	5.1	4.9
			1.25	8.1	7.2	6.5	5.9	7.9	7.1	6.4	5.9	7.6	6.9	6.3	5.9	7.4	6.7	6.2	5.8	5.6
下方投影面積			1.5	8.5	7.7	7.0	6.5	8.3	7.6	7.0	6.5	8.0	7.4	6.8	6.4	7.8	7.2	6.7	6.3	6.1
			2.0	9.1	8.4	7.8	7.3	8.9	8.3	7.7	7.3	8.6	8.1	7.6	7.2	8.3	7.9	7.5	7.1	6.9
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.3	7.9	9.2	8.7	8.3	7.9	8.9	8.5	8.1	7.8	8.7	8.3	8.0	7.7	7.4
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.7	8.3	9.5	9.0	8.6	8.3	9.2	8.8	8.5	8.2	8.9	8.6	8.3	8.0	7.8
Hm	1.26Hm	1.26Hm	4.0	9.9	9.5	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.7	9.2	9.0	8.8	8.5	8.3
			5.0	10.1	9.8	9.5	9.2	10.0	9.7	9.4	9.2	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.9	8.6
			7.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.7	9.6	9.4	9.7	9.5	9.4	9.2	8.9
			10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

