

# 屋内照明器具特性

品番 (品名)	XAD1100L	
光源	LLD2000LCS1 ×1	580.0 lm
管理番号	K0181857(0)DR1	
BZ分類	BZ4/0.7/BZ3	

器具効率	76%	天井	80%				70%				50%				30%				0%				
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
下方光束	76%	床	10%				10%				10%				10%				0%				
室指数			照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	4.6	3.8	3.2	2.9	4.6	3.8	3.2	2.9	4.4	3.7	3.2	2.9	4.2	3.6	3.2	2.8	2.7			
	中	0.63	0.8	5.4	4.6	4.1	3.7	5.3	4.6	4.1	3.7	5.1	4.5	4.0	3.7	4.9	4.4	4.0	3.7	3.5			
	否	0.56	1.0	5.9	5.2	4.7	4.3	5.8	5.1	4.6	4.3	5.6	5.0	4.6	4.2	5.4	4.9	4.5	4.2	4.1			
			1.25	6.3	5.7	5.2	4.8	6.2	5.6	5.2	4.8	6.0	5.5	5.1	4.8	5.8	5.4	5.0	4.7	4.6			
下方投影面積		cm <sup>2</sup>	1.5	6.6	6.0	5.6	5.2	6.5	6.0	5.6	5.2	6.3	5.8	5.5	5.2	6.1	5.7	5.4	5.1	5.0			
等価発光面積		cm <sup>2</sup>	2.0	7.0	6.5	6.1	5.8	6.9	6.5	6.1	5.8	6.7	6.3	6.0	5.7	6.5	6.2	5.9	5.7	5.5			
取付高さ	器具間隔最大限		2.5	7.2	6.8	6.5	6.2	7.1	6.8	6.4	6.2	6.9	6.6	6.3	6.1	6.7	6.5	6.2	6.0	5.9			
	横方向 (A)	縦方向 (B)	3.0	7.4	7.1	6.8	6.5	7.3	7.0	6.7	6.5	7.1	6.8	6.6	6.4	6.9	6.7	6.5	6.3	6.1			
Hm	1.20Hm	1.20Hm	4.0	7.6	7.3	7.1	6.9	7.5	7.2	7.0	6.8	7.3	7.1	6.9	6.7	7.1	6.9	6.8	6.6	6.4			
			5.0	7.7	7.5	7.3	7.1	7.6	7.4	7.2	7.1	7.4	7.3	7.1	6.9	7.2	7.1	7.0	6.8	6.6			
			7.0	7.9	7.7	7.5	7.4	7.8	7.6	7.5	7.3	7.6	7.4	7.3	7.2	7.4	7.3	7.2	7.1	6.9			
			10.0	8.0	7.8	7.7	7.6	7.9	7.8	7.7	7.6	7.7	7.6	7.5	7.4	7.5	7.4	7.4	7.3	7.1			

