

屋内照明器具特性

品番 (品名)	NNN13512															
光源	LED3500_70_1310 x1 1310.0 lm															
管理番号	K0180978(2)DR1															
BZ分類	BZ7/0.7/BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%												
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%												
		床	10%				10%				10%				10%				0%												
上方光束	43%																														
下方光束	57%																														
室指数	照明率 (X0.01) ZCM																														
保守率	良 中 否	0.63	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	48	35	28	22	44	33	26	21	37	29	23	18	31	24	20	16	11
		0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	48	35	28	22	44	33	26	21	37	29	23	18	31	24	20	16	11	
		0.56	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	48	35	28	22	44	33	26	21	37	29	23	18	31	24	20	16	11	
		0.56	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	48	35	28	22	44	33	26	21	37	29	23	18	31	24	20	16	11	
下方投影面積	c m ²																														
等価発光面積	c m ²																														
取付高さ	器具間隔最大限																														
	横方向 (A)	縦方向 (B)																													
1.5m	1.96m	1.91m	4.0	87	81	76	72	81	76	72	68	70	66	63	60	60	57	54	52	40											
2	2.61	2.51	5.0	89	84	80	76	83	79	75	72	72	69	66	63	62	59	57	55	42											
2.5	3.27	3.12	7.0	91	88	84	81	86	82	79	77	75	72	70	67	64	62	60	59	45											
3	3.9	3.73	10.0	93	91	88	86	88	85	83	81	76	75	73	71	66	64	63	62	48											

