

# 屋内照明器具特性

品番 (品名)	XAD3 1 0 1 N															
光源	LLD4000NCS1 ×1                      830.0 1 m															
管理番号	K0181861 ( 0 ) DR 1															
BZ分類	BZ4 / 0.9 / BZ3															

器具効率	54 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 ( X0.01 )																ZCM		
下方光束	54 %																				
保守率	良 0.67 中 0.63 否 0.56	0.6	3.2	2.6	2.2	2.0	3.2	2.6	2.2	2.0	3.1	2.6	2.2	2.0	2.9	2.5	2.2	2.0	1.9		
		0.8	3.8	3.2	2.9	2.6	3.7	3.2	2.8	2.6	3.6	3.1	2.8	2.6	3.5	3.1	2.8	2.6	2.4		
		1.0	4.2	3.6	3.3	3.0	4.1	3.6	3.3	3.0	3.9	3.5	3.2	3.0	3.8	3.5	3.2	3.0	2.9		
		1.25	4.5	4.0	3.7	3.4	4.4	4.0	3.7	3.4	4.2	3.9	3.6	3.4	4.1	3.8	3.6	3.4	3.2		
下方投影面積	c m <sup>2</sup>	1.5	4.7	4.3	4.0	3.7	4.6	4.2	3.9	3.7	4.4	4.1	3.9	3.7	4.3	4.0	3.8	3.6	3.5		
		2.0	4.9	4.6	4.3	4.1	4.9	4.6	4.3	4.1	4.7	4.5	4.2	4.1	4.6	4.4	4.2	4.0	3.9		
取付高さ	器具間隔最大限		2.5	5.1	4.8	4.6	4.4	5.0	4.8	4.6	4.4	4.9	4.7	4.5	4.3	4.8	4.6	4.4	4.3	4.1	
	横方向 (A)	縦方向 (B)	3.0	5.2	5.0	4.8	4.6	5.2	4.9	4.7	4.6	5.0	4.8	4.7	4.5	4.9	4.7	4.6	4.5	4.3	
H m	1.26 H m	1.26 H m	4.0	5.4	5.2	5.0	4.9	5.3	5.1	5.0	4.8	5.2	5.0	4.9	4.8	5.0	4.9	4.8	4.7	4.6	
			5.0	5.5	5.3	5.2	5.0	5.4	5.2	5.1	5.0	5.2	5.1	5.0	4.9	5.1	5.0	4.9	4.8	4.7	
			7.0	5.6	5.4	5.3	5.2	5.5	5.4	5.3	5.2	5.3	5.3	5.2	5.1	5.2	5.1	5.1	5.0	4.9	
			10.0	5.6	5.5	5.5	5.4	5.6	5.5	5.4	5.3	5.4	5.4	5.3	5.2	5.3	5.2	5.2	5.2	5.0	

