

屋内照明器具特性	
品番 (品名)	XAD3 1 0 1 V
光源	LLD4000VCS1 ×1 830.0 1 m
管理番号	K0181861 (0) DR 1
BZ分類	BZ4 / 0.9 / BZ3

器具効率	54 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	54 %	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	3.2	2.6	2.2	2.0	3.2	2.6	2.2	2.0	3.1	2.6	2.2	2.0	2.9	2.5	2.2	2.0	1.9			
	中	0.63	0.8	3.8	3.2	2.9	2.6	3.7	3.2	2.8	2.6	3.6	3.1	2.8	2.6	3.5	3.1	2.8	2.6	2.4			
	否	0.56	1.0	4.2	3.6	3.3	3.0	4.1	3.6	3.3	3.0	3.9	3.5	3.2	3.0	3.8	3.5	3.2	3.0	2.9			
			1.25	4.5	4.0	3.7	3.4	4.4	4.0	3.7	3.4	4.2	3.9	3.6	3.4	4.1	3.8	3.6	3.4	3.2			
下方投影面積		c m ²	1.5	4.7	4.3	4.0	3.7	4.6	4.2	3.9	3.7	4.4	4.1	3.9	3.7	4.3	4.0	3.8	3.6	3.5			
等価発光面積		c m ²	2.0	4.9	4.6	4.3	4.1	4.9	4.6	4.3	4.1	4.7	4.5	4.2	4.1	4.6	4.4	4.2	4.0	3.9			
取付高さ	器具間隔最大限		2.5	5.1	4.8	4.6	4.4	5.0	4.8	4.6	4.4	4.9	4.7	4.5	4.3	4.8	4.6	4.4	4.3	4.1			
	横方向 (A)	縦方向 (B)	3.0	5.2	5.0	4.8	4.6	5.2	4.9	4.7	4.6	5.0	4.8	4.7	4.5	4.9	4.7	4.6	4.5	4.3			
H m	1.26 H m	1.26 H m	4.0	5.4	5.2	5.0	4.9	5.3	5.1	5.0	4.8	5.2	5.0	4.9	4.8	5.0	4.9	4.8	4.7	4.6			
			5.0	5.5	5.3	5.2	5.0	5.4	5.2	5.1	5.0	5.2	5.1	5.0	4.9	5.1	5.0	4.9	4.8	4.7			
			7.0	5.6	5.4	5.3	5.2	5.5	5.4	5.3	5.2	5.3	5.3	5.2	5.1	5.2	5.1	5.1	5.0	4.9			
			10.0	5.6	5.5	5.5	5.4	5.6	5.5	5.4	5.3	5.4	5.4	5.3	5.2	5.3	5.2	5.2	5.2	5.0			

