

屋内照明器具特性

品番 (品名)	XAD3 1 0 1 L	
光源	LLD4000LCS1 ×1	830.0 lm
管理番号	K0181861 (0) DR 1	
BZ分類	BZ4 / 0.9 / BZ3	

器具効率	54 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		54 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	3.2	2.6	2.2	2.0	3.2	2.6	2.2	2.0	3.1	2.6	2.2	2.0	2.9	2.5	2.2	2.0	1.9	
	中	0.63	0.8	3.8	3.2	2.9	2.6	3.7	3.2	2.8	2.6	3.6	3.1	2.8	2.6	3.5	3.1	2.8	2.6	2.4	
	否	0.56	1.0	4.2	3.6	3.3	3.0	4.1	3.6	3.3	3.0	3.9	3.5	3.2	3.0	3.8	3.5	3.2	3.0	2.9	
			1.25	4.5	4.0	3.7	3.4	4.4	4.0	3.7	3.4	4.2	3.9	3.6	3.4	4.1	3.8	3.5	3.2	3.2	
下方投影面積	c m ²		1.5	4.7	4.3	4.0	3.7	4.6	4.2	3.9	3.7	4.4	4.1	3.9	3.7	4.3	4.0	3.8	3.6	3.5	
	等価発光面積		c m ²	2.0	4.9	4.6	4.3	4.1	4.9	4.6	4.3	4.1	4.7	4.5	4.2	4.1	4.6	4.4	4.2	4.0	3.9
取付高さ	器具間隔最大限		2.5	5.1	4.8	4.6	4.4	5.0	4.8	4.6	4.4	4.9	4.7	4.5	4.3	4.8	4.6	4.4	4.3	4.1	
	横方向 (A)	縦方向 (B)	3.0	5.2	5.0	4.8	4.6	5.2	4.9	4.7	4.6	5.0	4.8	4.7	4.5	4.9	4.7	4.6	4.5	4.3	
H m	1.26 H m	1.26 H m	4.0	5.4	5.2	5.0	4.9	5.3	5.1	5.0	4.8	5.2	5.0	4.9	4.8	5.0	4.9	4.8	4.7	4.6	
			5.0	5.5	5.3	5.2	5.0	5.4	5.2	5.1	5.0	5.2	5.1	5.0	4.9	5.1	5.0	4.9	4.8	4.7	
			7.0	5.6	5.4	5.3	5.2	5.5	5.4	5.3	5.2	5.3	5.3	5.2	5.1	5.2	5.1	5.1	5.0	4.9	
			10.0	5.6	5.5	5.5	5.4	5.6	5.5	5.4	5.3	5.4	5.4	5.3	5.2	5.3	5.2	5.2	5.2	5.0	

