

屋内照明器具特性

品番 (品名)	XAD1111VK														
光源	LLD2000MVCE1 ×1 531.0 lm														
管理番号	K0175548(0)DR1														
BZ分類	BZ4/0.7/BZ3														

器具効率	64%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01) ZCM																		
保守率	良 0.67 中 0.63 否 0.56	0.6	3.9	3.2	2.7	2.4	3.8	3.1	2.7	2.4	3.7	3.1	2.7	2.4	3.5	3.0	2.6	2.4	2.3		
		0.8	4.6	3.9	3.5	3.1	4.5	3.9	3.4	3.1	4.3	3.8	3.4	3.1	4.2	3.7	3.4	3.1	3.0		
		1.0	5.0	4.4	4.0	3.7	4.9	4.4	4.0	3.7	4.7	4.3	3.9	3.6	4.6	4.2	3.9	3.6	3.5		
		1.25	5.4	4.9	4.5	4.2	5.3	4.8	4.4	4.1	5.1	4.7	4.4	4.1	5.0	4.6	4.3	4.1	3.9		
下方投影面積	c m ²	1.5	5.6	5.2	4.8	4.5	5.5	5.1	4.8	4.5	5.4	5.0	4.7	4.4	5.2	4.9	4.6	4.4	4.3		
		2.0	5.9	5.6	5.2	5.0	5.9	5.5	5.2	5.0	5.7	5.4	5.1	4.9	5.5	5.3	5.0	4.9	4.7		
取付高さ	器具間隔最大限		2.5	6.1	5.8	5.5	5.3	6.0	5.8	5.5	5.3	5.9	5.6	5.4	5.2	5.7	5.5	5.3	5.2	5.0	
	横方向 (A)	縦方向 (B)	3.0	6.3	6.0	5.8	5.5	6.2	5.9	5.7	5.5	6.0	5.8	5.6	5.4	5.9	5.7	5.5	5.4	5.2	
H m	1.25 H m	1.25 H m	4.0	6.4	6.2	6.0	5.8	6.3	6.1	6.0	5.8	6.2	6.0	5.9	5.7	6.0	5.9	5.8	5.6	5.5	
			5.0	6.5	6.4	6.2	6.0	6.4	6.3	6.1	6.0	6.3	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.6	
			7.0	6.6	6.5	6.4	6.3	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	5.8	
			10.0	6.7	6.6	6.5	6.5	6.6	6.6	6.5	6.4	6.5	6.4	6.4	6.3	6.3	6.3	6.2	6.2	6.0	

