

屋内照明器具特性

| | | |
|---------|-------------------|----------|
| 品番 (品名) | XAD3 200 V | |
| 光源 | LLD4000VCS1 ×1 | 830.0 lm |
| 管理番号 | K0181859 (0) DR 1 | |
| BZ分類 | BZ4 / 0.9 / BZ3 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|-------------------------------------|----------|---------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|
| 器具効率 | 83 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % | |
| 上方光束 | 0 % | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | |
| 下方光束 | 83 % | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 中 否 0.67 0.63 0.56 | 0.6 | 51 | 41 | 35 | 31 | 50 | 41 | 35 | 31 | 48 | 40 | 35 | 31 | 46 | 39 | 34 | 31 | 29 | |
| | | 0.8 | 59 | 50 | 45 | 40 | 58 | 50 | 44 | 40 | 56 | 49 | 44 | 40 | 54 | 48 | 43 | 40 | 38 | |
| | | 1.0 | 65 | 57 | 51 | 47 | 63 | 56 | 51 | 47 | 61 | 55 | 50 | 46 | 59 | 54 | 50 | 46 | 45 | |
| | | 1.25 | 69 | 62 | 57 | 53 | 68 | 62 | 57 | 53 | 66 | 60 | 56 | 53 | 64 | 59 | 55 | 52 | 50 | |
| 下方投影面積 | c m ² | 1.5 | 73 | 66 | 62 | 58 | 71 | 66 | 61 | 57 | 69 | 64 | 60 | 57 | 67 | 63 | 59 | 56 | 55 | |
| | | 2.0 | 77 | 72 | 68 | 64 | 76 | 71 | 67 | 64 | 73 | 69 | 66 | 63 | 71 | 68 | 65 | 62 | 61 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 80 | 75 | 72 | 68 | 78 | 74 | 71 | 68 | 76 | 73 | 70 | 67 | 74 | 71 | 69 | 66 | 65 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 81 | 78 | 74 | 72 | 80 | 77 | 74 | 71 | 78 | 75 | 72 | 70 | 76 | 73 | 71 | 69 | 67 |
| H m | 1.26 H m | 1.26 H m | 4.0 | 83 | 81 | 78 | 76 | 82 | 80 | 77 | 75 | 80 | 78 | 76 | 74 | 78 | 76 | 75 | 73 | 71 |
| | | | 5.0 | 85 | 82 | 80 | 78 | 84 | 81 | 79 | 78 | 82 | 80 | 78 | 76 | 80 | 78 | 77 | 75 | 73 |
| | | | 7.0 | 86 | 85 | 83 | 81 | 85 | 84 | 82 | 81 | 83 | 82 | 81 | 79 | 81 | 80 | 79 | 78 | 76 |
| | | | 10.0 | 87 | 86 | 85 | 84 | 86 | 85 | 84 | 83 | 84 | 83 | 82 | 82 | 82 | 82 | 81 | 80 | 78 |

