

屋内照明器具特性

品番 (品名)	XAD3 1 2 2 LK	
光源	LLD3020LCE1 ×1	795.0 1m
管理番号	K0175544 (0) DR 1	
BZ分類	BZ1	

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %					
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
下方光束	68 %	床		10 %				10 %				10 %				10 %				0 %				
室指数	照明率 (X0.01)																			ZCM				
保守率	良 0.67	0.6	0.6	57	52	50	48	56	52	50	48	55	52	49	48	54	51	49	48	47				
	中 0.63		0.8	61	57	54	53	60	57	54	52	59	56	54	52	58	56	54	52	51				
	否 0.56		1.0	63	60	57	56	63	59	57	55	61	59	57	55	60	58	56	55	54				
下方投影面積	c m ²	等価発光面積	c m ²	1.25	65	62	60	58	65	62	60	58	63	61	59	58	62	60	59	57	56			
				1.5	67	64	62	60	66	63	62	60	65	63	61	60	63	62	60	59	58	57	56	
取付高さ	器具間隔最大限		H m	0.41 H m	H m	0.41 H m	2.5	69	68	66	65	69	67	66	64	67	66	65	64	66	65	64	63	62
	横方向 (A)	縦方向 (B)					3.0	70	68	67	66	69	68	67	66	68	67	66	65	67	66	65	64	63
H m	0.41 H m	0.41 H m	4.0	71	70	69	68	70	69	68	67	69	68	67	66	67	67	66	65	64	64	64	64	
			5.0	71	70	69	69	71	70	69	68	69	68	68	67	68	67	67	67	66	65	65	65	65
			7.0	72	71	71	70	71	71	70	69	70	69	69	68	68	68	68	68	67	67	65	65	65
10.0	72	72	71	71	72	71	71	70	70	70	69	69	69	69	68	68	68	68	66	66	66	66		

