

# 屋内照明器具特性

|         |                     |           |
|---------|---------------------|-----------|
| 品番 (品名) | XAD3 1 2 2 NK       |           |
| 光源      | LLD3 0 2 0 NCE1 × 1 | 795.0 l m |
| 管理番号    | K0175544 ( 0 ) DR 1 |           |
| B Z 分類  | B Z 1               |           |

|        |           |                  |                |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |       |     |
|--------|-----------|------------------|----------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-------|-----|
| 器具効率   | 68 %      | 天井               | 80 %           |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 %   |     |
|        | 上方光束      |                  | 0 %            | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10    | 0 % |
| 下方光束   | 68 %      | 床                | 10 %           |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 %   |     |
| 室指数    |           |                  | 照明率 ( X 0.01 ) |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    | Z C M |     |
| 保守率    | 良         | 0.67             | 0.6            | 57 | 52 | 50 | 48   | 56 | 52 | 50 | 48   | 55 | 52 | 49 | 48   | 54 | 51 | 49 | 48    | 47  |
|        | 中         | 0.63             | 0.8            | 61 | 57 | 54 | 53   | 60 | 57 | 54 | 52   | 59 | 56 | 54 | 52   | 58 | 56 | 54 | 52    | 51  |
|        | 否         | 0.56             | 1.0            | 63 | 60 | 57 | 56   | 63 | 59 | 57 | 55   | 61 | 59 | 57 | 55   | 60 | 58 | 56 | 55    | 54  |
| 下方投影面積 | 等価発光面積    | c m <sup>2</sup> | 1.25           | 65 | 62 | 60 | 58   | 65 | 62 | 60 | 58   | 63 | 61 | 59 | 58   | 62 | 60 | 59 | 57    | 56  |
|        |           |                  | 1.5            | 67 | 64 | 62 | 60   | 66 | 63 | 62 | 60   | 65 | 63 | 61 | 60   | 63 | 62 | 60 | 59    | 58  |
| 取付高さ   | 器具間隔最大限   |                  | 2.5            | 69 | 68 | 66 | 65   | 69 | 67 | 66 | 64   | 67 | 66 | 65 | 64   | 66 | 65 | 64 | 63    | 62  |
|        | 横方向 ( A ) | 縦方向 ( B )        | 3.0            | 70 | 68 | 67 | 66   | 69 | 68 | 67 | 66   | 68 | 67 | 66 | 65   | 67 | 66 | 65 | 64    | 63  |
| H m    | 0.41 H m  | 0.41 H m         | 4.0            | 71 | 70 | 69 | 68   | 70 | 69 | 68 | 67   | 69 | 68 | 67 | 66   | 67 | 67 | 66 | 65    | 64  |
|        |           |                  | 5.0            | 71 | 70 | 69 | 69   | 71 | 70 | 69 | 68   | 69 | 68 | 68 | 67   | 68 | 67 | 67 | 66    | 65  |
|        |           |                  | 7.0            | 72 | 71 | 71 | 70   | 71 | 71 | 70 | 69   | 70 | 69 | 69 | 68   | 68 | 68 | 67 | 67    | 65  |
|        |           |                  | 10.0           | 72 | 72 | 71 | 71   | 72 | 71 | 71 | 70   | 70 | 70 | 69 | 69   | 69 | 68 | 68 | 68    | 66  |

