

屋内照明器具特性

品番 (品名)	LGB57652	
光源	LDA4L-H/S/4 ×6	485.0 lm
管理番号	K0178893(0)DB1	
BZ分類	BZ2/1.1/BZ3/3.5/BZ4	

器具効率	35%	天井	80%				70%				50%				30%				0%		
	上方光束		2%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		33%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	23	20	17	16	23	19	17	16	22	19	17	16	21	18	17	15	15	
	中	0.63	0.8	26	23	21	19	25	22	20	19	24	22	20	19	23	21	20	18	18	
	否	0.56	1.0	28	25	23	21	27	25	23	21	26	24	22	21	25	23	22	20	19	
			1.25	29	27	25	23	29	26	24	23	28	26	24	23	26	25	23	22	21	
下方投影面積 等価発光面積	c m ²		1.5	31	28	26	25	30	28	26	24	29	27	25	24	27	26	25	24	22	
	c m ²		2.0	32	30	28	27	31	29	28	27	30	28	27	26	29	28	26	25	24	
	c m ²		2.5	33	31	30	28	32	31	29	28	31	30	28	27	30	29	28	27	25	
取付高さ	器具間隔最大限		H m	横方向 (A)		縦方向 (B)															
	H m			1.07 H m		1.07 H m															
			4.0	35	33	32	31	34	33	32	31	32	31	31	30	31	30	30	29	28	
			5.0	35	34	33	32	34	33	32	32	33	32	31	31	32	31	30	30	28	
			7.0	36	35	34	33	35	34	33	33	34	33	32	32	32	32	31	31	29	
			10.0	36	36	35	34	35	35	34	34	34	34	33	33	33	32	32	32	30	

