

屋内照明器具特性	
品番 (品名)	LGB11402
光源	LDA7L-D-G/S/Z6 ×3      810.0 lm
管理番号	K0183313(0)DB1
BZ分類	BZ7

器具効率	95%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	46%	反射率	床	10%				10%				10%				10%				0%
下方光束	49%		室指数	照明率 (X0.01)																ZCM
保守率	良	0.63	0.6	4.4	3.2	2.5	2.0	4.0	3.0	2.3	1.9	3.4	2.5	2.0	1.6	2.7	2.1	1.7	1.3	0.9
	中	0.6	0.8	5.2	4.1	3.3	2.7	4.8	3.8	3.1	2.5	4.0	3.2	2.6	2.2	3.2	2.6	2.2	1.8	1.2
	否	0.56	1.0	5.7	4.7	3.9	3.3	5.3	4.3	3.6	3.1	4.4	3.6	3.1	2.6	3.6	3.0	2.6	2.2	1.5
			1.25	6.3	5.2	4.5	3.9	5.7	4.8	4.2	3.6	4.8	4.1	3.5	3.1	3.9	3.4	2.9	2.6	1.8
下方投影面積		cm <sup>2</sup>	1.5	6.6	5.7	4.9	4.4	6.1	5.3	4.6	4.1	5.1	4.4	3.9	3.5	4.2	3.7	3.3	2.9	2.0
等価発光面積		cm <sup>2</sup>	2.0	7.1	6.3	5.7	5.1	6.6	5.9	5.3	4.8	5.5	5.0	4.5	4.1	4.5	4.1	3.7	3.4	2.4
取付高さ	器具間隔最大限		2.5	7.5	6.8	6.1	5.6	6.9	6.3	5.7	5.2	5.8	5.3	4.9	4.5	4.8	4.4	4.1	3.8	2.6
	横方向 (A)	縦方向 (B)	3.0	7.7	7.1	6.5	6.0	7.1	6.6	6.1	5.6	6.0	5.6	5.2	4.8	5.0	4.6	4.3	4.1	2.8
H <sub>m</sub>	1.44H <sub>m</sub>	1.44H <sub>m</sub>	4.0	8.0	7.5	7.0	6.6	7.4	7.0	6.5	6.2	6.3	5.9	5.6	5.3	5.2	4.9	4.7	4.4	3.2
			5.0	8.2	7.8	7.4	7.0	7.6	7.2	6.9	6.5	6.5	6.2	5.9	5.6	5.4	5.2	4.9	4.7	3.4
			7.0	8.5	8.1	7.8	7.5	7.9	7.6	7.3	7.0	6.7	6.5	6.2	6.0	5.6	5.4	5.2	5.1	3.7
			10.0	8.7	8.4	8.2	7.9	8.1	7.8	7.6	7.4	6.9	6.7	6.5	6.4	5.8	5.7	5.5	5.4	3.9

