

|          |   |
|----------|---|
| 屋内照明器具特性 |   |
| 品番 (品名)  | LGB19305Z                                     |
| 光源       | LDA7L-G/S/K6 ×2                      810.0 lm |
| 管理番号     | K0160392(0)DR1                                |
| BZ分類     | BZ5/1.4/BZ6                                   |

|        |                            |         |               |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|--------|----------------------------|---------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率   | 56%                        | 天井      | 80%           |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|        |                            | 壁       | 70            | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 19%                        | 床       | 10%           |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束   | 37%                        | 室指数     | 照明率 ( X0.01 ) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率    | 良 0.67<br>中 0.63<br>否 0.56 | 0.6     | 28            | 22 | 17 | 14 | 27  | 21 | 17 | 14 | 23  | 18 | 15 | 13 | 20  | 16 | 14 | 12 | 9   |    |
|        |                            | 0.8     | 33            | 27 | 22 | 19 | 31  | 25 | 21 | 18 | 27  | 23 | 19 | 17 | 24  | 20 | 18 | 15 | 13  |    |
|        |                            | 1.0     | 36            | 30 | 26 | 23 | 34  | 29 | 25 | 22 | 30  | 26 | 23 | 20 | 26  | 23 | 20 | 18 | 15  |    |
|        |                            | 1.25    | 39            | 34 | 30 | 26 | 37  | 32 | 28 | 25 | 33  | 29 | 25 | 23 | 29  | 25 | 23 | 21 | 17  |    |
| 下方投影面積 | c m <sup>2</sup>           | 1.5     | 42            | 36 | 32 | 29 | 39  | 34 | 31 | 28 | 34  | 31 | 28 | 25 | 30  | 27 | 25 | 23 | 19  |    |
|        |                            | 2.0     | 44            | 40 | 36 | 33 | 42  | 38 | 34 | 32 | 37  | 34 | 31 | 29 | 32  | 30 | 28 | 26 | 21  |    |
| 取付高さ   | 器具間隔最大限                    |         | 2.5           | 46 | 42 | 39 | 36  | 44 | 40 | 37 | 34  | 39 | 36 | 33 | 31  | 34 | 32 | 30 | 28  | 23 |
|        | 横方向 (A)                    | 縦方向 (B) | 3.0           | 48 | 44 | 41 | 38  | 45 | 42 | 39 | 37  | 40 | 37 | 35 | 33  | 35 | 33 | 31 | 30  | 24 |
| H m    | 1.33H m                    | 1.33H m | 4.0           | 49 | 46 | 44 | 41  | 47 | 44 | 42 | 40  | 41 | 39 | 37 | 36  | 37 | 35 | 33 | 32  | 26 |
|        |                            |         | 5.0           | 50 | 48 | 46 | 44  | 48 | 45 | 43 | 42  | 43 | 41 | 39 | 38  | 38 | 36 | 35 | 34  | 28 |
|        |                            |         | 7.0           | 52 | 50 | 48 | 46  | 49 | 47 | 46 | 44  | 44 | 42 | 41 | 40  | 39 | 38 | 37 | 36  | 29 |
|        |                            |         | 10.0          | 53 | 51 | 50 | 49  | 50 | 49 | 48 | 46  | 45 | 44 | 43 | 42  | 40 | 39 | 38 | 37  | 31 |

