

| | |
|----------|----------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | LRD1108L |
| 光源 | LED2700_70_450 x1 450.0 lm |
| 管理番号 | K0159976(0)D 1 |
| BZ分類 | BZ3 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 0% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 100% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.67 | 0.6 | 62 | 51 | 44 | 39 | 61 | 50 | 44 | 39 | 59 | 49 | 43 | 39 | 57 | 48 | 43 | 39 | 37 |
| | 中 | 0.63 | 0.8 | 72 | 62 | 56 | 51 | 71 | 62 | 55 | 51 | 69 | 61 | 55 | 50 | 66 | 59 | 54 | 50 | 48 |
| | 否 | 0.56 | 1.0 | 79 | 70 | 64 | 59 | 78 | 69 | 63 | 59 | 75 | 68 | 62 | 58 | 73 | 67 | 62 | 58 | 56 |
| | | | 1.25 | 85 | 77 | 71 | 66 | 84 | 76 | 70 | 66 | 81 | 75 | 70 | 66 | 78 | 73 | 69 | 65 | 63 |
| 下方投影面積 | cm ² | | 1.5 | 89 | 82 | 76 | 72 | 87 | 81 | 75 | 71 | 85 | 79 | 74 | 71 | 82 | 77 | 73 | 70 | 68 |
| | 等価発光面積 | | 2.0 | 94 | 88 | 83 | 79 | 92 | 87 | 82 | 79 | 90 | 85 | 81 | 78 | 87 | 83 | 80 | 77 | 75 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 97 | 92 | 88 | 84 | 95 | 91 | 87 | 84 | 93 | 89 | 85 | 83 | 90 | 87 | 84 | 82 | 79 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 99 | 94 | 91 | 88 | 97 | 93 | 90 | 87 | 95 | 91 | 88 | 86 | 92 | 89 | 87 | 85 | 82 |
| Hm | 1.20Hm | 1.19Hm | 4.0 | 101 | 98 | 95 | 92 | 100 | 97 | 94 | 92 | 97 | 95 | 92 | 90 | 95 | 93 | 91 | 89 | 86 |
| | | | 5.0 | 102 | 100 | 97 | 95 | 101 | 99 | 96 | 94 | 99 | 97 | 95 | 93 | 96 | 95 | 93 | 92 | 89 |
| | | | 7.0 | 104 | 102 | 100 | 99 | 103 | 101 | 99 | 98 | 100 | 99 | 97 | 96 | 98 | 97 | 96 | 95 | 92 |
| | | | 10.0 | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99 | 99 | 99 | 98 | 97 | 94 |

