

屋内照明器具特性	
品番 (品名)	L G W8 5 2 3 9 B
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0180435 (0) DR 1
B Z 分類	B Z 5

器具効率	56%	天井	80%				70%				50%				30%				0%		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	5%	反射率	床		10%		10%		10%		10%		10%		10%		0%				
下方光束	51%		室指数																		
		照明率 (X0.01)																			ZCM
保守率	良 0.63 中 0.6 否 0.56	0.6	31	24	20	17	30	23	19	16	28	22	19	16	26	22	18	16	14		
		0.8	36	30	25	22	35	29	25	22	33	28	24	21	31	27	23	21	19		
		1.0	40	34	29	26	39	33	29	26	36	32	28	25	34	30	27	24	23		
		1.25	43	38	33	30	42	37	33	30	39	35	32	29	37	33	31	28	26		
下方投影面積	c m ²	1.5	45	40	36	33	44	39	36	33	42	38	34	32	39	36	33	31	29		
		2.0	49	44	41	38	47	43	40	37	45	41	38	36	42	39	37	35	33		
取付高さ	器具間隔最大限		2.5	51	47	44	41	49	46	43	40	47	44	41	39	44	42	40	38	35	
	横方向 (A)	縦方向 (B)	3.0	52	49	46	43	51	47	45	42	48	45	43	41	46	43	41	40	37	
H m	1.24 H m	1.25 H m	4.0	54	51	49	46	52	50	48	46	50	48	46	44	47	46	44	43	40	
			5.0	55	53	50	49	54	51	50	48	51	49	48	46	49	47	46	45	42	
			7.0	56	54	53	51	55	53	52	50	52	51	50	49	50	49	48	47	44	
			10.0	57	56	55	54	56	55	54	53	53	52	51	51	51	50	49	49	46	

