

屋内照明器具特性	
品番(品名)	LGW85239B
光源	LLD2020LCE1 ×1                      460.0 lm
管理番号	K0180436(0)DR1
BZ分類	BZ5

器具効率	51%	天井	80%				70%				50%				30%				0%																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
		床	10%				10%				10%				10%				0%																																							
上方光束	4%	室指数																			照明率 (×0.01)																			ZCM																		
下方光束	47%																																																									
保守率	良 0.63 中 0.6 否 0.56	0.6	2.8	2.1	1.7	1.5	2.7	2.1	1.7	1.4	2.5	2.0	1.7	1.4	2.4	1.9	1.6	1.4	1.3																																							
		0.8	3.2	2.6	2.2	1.9	3.1	2.6	2.2	1.9	3.0	2.5	2.1	1.9	2.8	2.4	2.1	1.8	1.7																																							
		1.0	3.6	3.0	2.6	2.3	3.5	2.9	2.5	2.3	3.3	2.8	2.5	2.2	3.1	2.7	2.4	2.2	2.0																																							
		1.25	3.9	3.3	2.9	2.6	3.7	3.3	2.9	2.6	3.5	3.1	2.8	2.5	3.3	3.0	2.7	2.5	2.3																																							
下方投影面積	cm <sup>2</sup>	1.5	4.1	3.6	3.2	2.9	4.0	3.5	3.2	2.9	3.7	3.4	3.0	2.8	3.5	3.2	2.9	2.7	2.5																																							
		2.0	4.4	3.9	3.6	3.3	4.2	3.9	3.5	3.3	4.0	3.7	3.4	3.2	3.8	3.5	3.3	3.1	2.9																																							
取付高さ	器具間隔最大限		2.5	4.5	4.2	3.9	3.6	4.4	4.1	3.8	3.6	4.2	3.9	3.7	3.5	4.0	3.7	3.5	3.4	3.2																																						
	横方向(A)	縦方向(B)	3.0	4.7	4.4	4.1	3.8	4.6	4.3	4.0	3.8	4.3	4.1	3.9	3.7	4.1	3.9	3.7	3.6	3.3																																						
Hm	1.19Hm	1.19Hm	4.0	4.8	4.6	4.4	4.2	4.7	4.5	4.3	4.1	4.5	4.3	4.1	4.0	4.3	4.1	4.0	3.8	3.6																																						
			5.0	4.9	4.7	4.5	4.4	4.8	4.6	4.5	4.3	4.6	4.4	4.3	4.1	4.4	4.3	4.1	4.0	3.8																																						
			7.0	5.1	4.9	4.8	4.6	5.0	4.8	4.7	4.5	4.7	4.6	4.5	4.4	4.5	4.4	4.3	4.2	4.0																																						
			10.0	5.2	5.0	4.9	4.8	5.1	4.9	4.8	4.7	4.8	4.8	4.7	4.6	4.6	4.6	4.5	4.4	4.2																																						

