

# 屋内照明器具特性

品番 (品名)	L G W 8 5 2 3 9 B														
光源	LLD3020MLCB1 ×1                      715.0 lm														
管理番号	K0180438 (0) DR 1														
BZ分類	BZ5														

器具効率	50%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	4%	室指数	照明率 ( X0.01)																ZCM		
下方光束	46%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	27	21	17	14	26	21	17	14	25	20	16	14	23	19	16	14	12		
		0.8	32	26	22	19	31	25	22	19	29	24	21	18	27	23	20	18	17		
		1.0	35	30	26	22	34	29	25	22	32	28	24	22	30	26	24	21	20		
		1.25	38	33	29	26	37	32	29	26	35	31	28	25	33	29	27	24	23		
下方投影面積	c m <sup>2</sup>	1.5	40	35	32	29	39	35	31	28	37	33	30	28	35	32	29	27	25		
		2.0	43	39	36	33	42	38	35	32	40	36	34	31	37	35	33	31	29		
取付高さ	器具間隔最大限		2.5	45	41	38	36	44	40	38	35	41	39	36	34	39	37	35	33		
	横方向 (A)	縦方向 (B)	3.0	46	43	40	38	45	42	39	37	43	40	38	36	40	38	37	35		
H m	1.20 H m	1.20 H m	4.0	48	45	43	41	47	44	42	40	44	42	41	39	42	41	39	38		
			5.0	49	47	45	43	48	46	44	42	45	44	42	41	43	42	41	40		
			7.0	50	48	47	45	49	47	46	45	47	45	44	43	45	44	43			
			10.0	51	50	49	48	50	49	48	47	48	47	46	45	46	45	44			

