

# 屋内照明器具特性

品番 (品名)	L G W 8 5 2 3 9 S															
光源	LLD3020LCE1 ×1                      795.0 l m															
管理番号	K0180437 ( 0 ) DR 1															
B Z 分類	B Z 5															

器具効率	47 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	4 %																			
下方光束	43 %																			
室指数	照明率 ( X 0.01 )                      Z C M																			
保守率	良 0.63 中 0.6 否 0.56	0.6	2.5	1.9	1.6	1.3	2.4	1.9	1.5	1.3	2.3	1.8	1.5	1.3	2.2	1.7	1.5	1.3	1.1	
		0.8	3.0	2.4	2.0	1.7	2.9	2.3	2.0	1.7	2.7	2.2	1.9	1.7	2.5	2.2	1.9	1.7	1.5	
		1.0	3.2	2.7	2.3	2.1	3.1	2.7	2.3	2.0	3.0	2.5	2.2	2.0	2.8	2.4	2.2	1.9	1.8	
		1.25	3.5	3.0	2.7	2.4	3.4	3.0	2.6	2.4	3.2	2.8	2.5	2.3	3.0	2.7	2.5	2.2	2.1	
下方投影面積	c m <sup>2</sup>	1.5	3.7	3.3	2.9	2.6	3.6	3.2	2.9	2.6	3.4	3.0	2.8	2.5	3.2	2.9	2.7	2.5	2.3	
		2.0	4.0	3.6	3.3	3.0	3.9	3.5	3.2	3.0	3.6	3.4	3.1	2.9	3.4	3.2	3.0	2.8	2.6	
		2.5	4.1	3.8	3.5	3.3	4.0	3.7	3.5	3.2	3.8	3.6	3.3	3.1	3.6	3.4	3.2	3.1	2.9	
取付高さ	器具間隔最大限																			
	横方向 ( A )	縦方向 ( B )																		
H m	1.20 H m	1.20 H m	4.0	4.4	4.2	4.0	3.8	4.3	4.1	3.9	3.7	4.1	3.9	3.7	3.6	3.9	3.7	3.6	3.5	3.3
			5.0	4.5	4.3	4.1	4.0	4.4	4.2	4.0	3.9	4.2	4.0	3.9	3.8	4.0	3.9	3.8	3.6	3.4
			7.0	4.6	4.5	4.3	4.2	4.5	4.4	4.2	4.1	4.3	4.2	4.1	4.0	4.1	4.0	3.9	3.8	3.6
			10.0	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.3	4.4	4.3	4.2	4.2	4.2	4.2	4.1	4.0	3.8

