

屋内照明器具特性

品番 (品名)	L G W8 5 2 3 9 S	
光源	LLD4000MLCE1 ×1	845.0 l m
管理番号	K0180428 (1) DR 1	
B Z 分類	B Z 5	

器具効率	56 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	5 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	51 %	室指数	照明率 (X0.01)																Z C M	
保守率	良	0.63	0.6	31	24	20	16	30	23	19	16	28	22	19	16	26	21	18	16	14
	中	0.6	0.8	36	30	25	22	35	29	25	22	33	28	24	21	31	26	23	21	19
	否	0.56	1.0	40	34	29	26	38	33	29	26	36	31	28	25	34	30	27	24	22
			1.25	43	37	33	30	42	36	33	29	39	35	31	29	37	33	30	28	26
下方投影面積		cm ²	1.5	45	40	36	33	44	39	35	32	41	37	34	32	39	36	33	31	28
等価発光面積		cm ²	2.0	48	44	40	37	47	43	40	37	44	41	38	36	42	39	37	35	32
取付高さ	器具間隔最大限		2.5	50	47	43	41	49	45	42	40	46	43	41	39	44	41	39	37	35
	横方向 (A)	縦方向 (B)	3.0	52	48	45	43	50	47	45	42	48	45	43	41	45	43	41	40	37
H m	1.24 H m	1.24 H m	4.0	53	51	48	46	52	50	47	45	49	47	46	44	47	45	44	42	40
			5.0	55	52	50	48	53	51	49	48	51	49	47	46	48	47	45	44	41
			7.0	56	54	53	51	55	53	51	50	52	51	49	48	50	48	47	46	44
			10.0	57	56	54	53	56	54	53	52	53	52	51	50	51	50	49	48	45

