

屋内照明器具特性	
品番(品名)	LGW85239Y
光源	LLD4300LCF1 ×1 930.0lm
管理番号	K0180426(2)DR1
BZ分類	BZ6

器具効率	72%	天井	80%				70%				50%				30%				0%				
	上方光束		13%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		59%		床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	3.7	2.8	2.2	1.8	3.5	2.7	2.2	1.8	3.2	2.5	2.0	1.7	3.0	2.3	1.9	1.6	1.4			
	中	0.6	0.8	4.4	3.5	2.9	2.5	4.2	3.4	2.8	2.4	3.8	3.1	2.7	2.3	3.5	2.9	2.5	2.2	1.9			
	否	0.56	1.0	4.8	4.0	3.4	2.9	4.6	3.9	3.3	2.9	4.2	3.6	3.1	2.7	3.9	3.4	2.9	2.6	2.3			
			1.25	5.2	4.5	3.9	3.5	5.0	4.3	3.8	3.4	4.6	4.0	3.6	3.2	4.2	3.8	3.4	3.1	2.7			
下方投影面積	cm ²		1.5	5.5	4.8	4.3	3.8	5.3	4.7	4.2	3.7	4.9	4.3	3.9	3.6	4.5	4.0	3.7	3.4	3.0			
	等価発光面積		2.0	5.9	5.3	4.8	4.4	5.7	5.2	4.7	4.3	5.3	4.8	4.4	4.1	4.9	4.5	4.2	3.9	3.5			
取付高さ	器具間隔最大限		2.5	6.2	5.7	5.2	4.8	6.0	5.5	5.1	4.7	5.5	5.1	4.8	4.5	5.1	4.8	4.5	4.2	3.8			
	横方向(A)	縦方向(B)	3.0	6.4	5.9	5.5	5.2	6.2	5.7	5.3	5.0	5.7	5.3	5.0	4.8	5.3	5.0	4.7	4.5	4.0			
Hm	1.38Hm	1.38Hm	4.0	6.6	6.2	5.9	5.6	6.4	6.0	5.7	5.4	5.9	5.7	5.4	5.2	5.5	5.3	5.1	4.9	4.4			
			5.0	6.8	6.5	6.2	5.9	6.5	6.3	6.0	5.7	6.1	5.9	5.6	5.4	5.7	5.5	5.3	5.1	4.6			
			7.0	7.0	6.7	6.5	6.3	6.7	6.5	6.3	6.1	6.3	6.1	5.9	5.7	5.9	5.7	5.6	5.4	4.9			
			10.0	7.1	6.9	6.7	6.6	6.9	6.7	6.5	6.4	6.4	6.3	6.2	6.0	6.0	5.9	5.8	5.7	5.1			

