

屋内照明器具特性

品番 (品名)	LGB81878															
光源	LED3500_70_1990 x1 1990.0 1m															
管理番号	K0174240(0)DR1															
BZ分類	BZ7															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	31%	室指数																			
下方光束	69%	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.67	0.6	47	35	26	21	44	33	25	20	39	29	23	18	34	26	20	16	12	
		0.63	0.8	56	43	35	28	53	41	33	27	46	37	30	25	40	32	27	22	17	
			1.0	62	50	41	35	58	47	39	33	51	42	35	30	44	37	32	27	21	
		0.56	1.25	68	56	48	41	64	53	45	39	56	47	41	36	49	42	37	32	25	
下方投影面積	c m ²	1.5	72	61	53	46	67	58	50	44	59	52	45	40	52	46	40	36	29		
		2.0	77	68	60	54	73	65	58	52	64	58	52	47	57	51	46	42	34		
取付高さ	器具間隔最大限		2.5	81	73	66	60	77	69	63	57	68	62	57	52	60	55	51	47	38	
	横方向 (A)	縦方向 (B)	3.0	84	76	70	64	79	72	67	62	70	65	60	56	62	58	54	50	41	
1.5m	2.16m	2.15m	4.0	87	81	76	71	83	77	72	68	74	69	65	61	65	62	59	55	46	
2	2.85	2.72	5.0	90	84	80	75	85	80	76	72	76	72	69	65	68	65	62	59	49	
2.5	3.53	3.31	7.0	93	88	84	81	88	84	81	77	79	76	73	70	71	68	66	63	53	
3	4.23	3.91	10.0	95	92	89	86	90	87	85	82	81	79	77	74	73	71	69	67	56	

