

屋内照明器具特性

品番 (品名)	LGB81879										
光源	LED2700_70_1820 x1 1820.0 lm										
管理番号	K0174240(0)DR1										
BZ分類	BZ7										

器具効率	100%	天井	80%				70%				50%				30%				0%																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																	
		床	10%				10%				10%				10%				0%																																	
上方光束	31%	室指数																	照明率 (X0.01)																	ZCM																
下方光束	69%																																																			
保守率	良 中 否	0.67	0.6	47	35	26	21	44	33	25	20	39	29	23	18	34	26	20	16	12																																
		0.63	0.8	56	43	35	28	53	41	33	27	46	37	30	25	40	32	27	22	17																																
			1.0	62	50	41	35	58	47	39	33	51	42	35	30	44	37	32	27	21																																
		0.56	1.25	68	56	48	41	64	53	45	39	56	47	41	36	49	42	37	32	25																																
下方投影面積	c m ²	1.5	72	61	53	46	67	58	50	44	59	52	45	40	52	46	40	36	29																																	
		2.0	77	68	60	54	73	65	58	52	64	58	52	47	57	51	46	42	34																																	
等価発光面積	c m ²	2.5	81	73	66	60	77	69	63	57	68	62	57	52	60	55	51	47	38																																	
		3.0	84	76	70	64	79	72	67	62	70	65	60	56	62	58	54	50	41																																	
取付高さ	器具間隔最大限		4.0	87	81	76	71	83	77	72	68	74	69	65	61	65	62	59	55	46																																
	横方向 (A)	縦方向 (B)	5.0	90	84	80	75	85	80	76	72	76	72	69	65	68	65	62	59	49																																
1.5m	2.16m	2.15m	7.0	93	88	84	81	88	84	81	77	79	76	73	70	71	68	66	63	53																																
2	2.85	2.72	10.0	95	92	89	86	90	87	85	82	81	79	77	74	73	71	69	67	56																																
2.5	3.53	3.31																																																		
3	4.23	3.91																																																		

