

屋内照明器具特性

品番 (品名)	FYY26675J															
光源	LED3000_85_3490 x1 3490.0 lm															
管理番号	K0176825(1)DB1															
BZ分類	BZ6/1.4/BZ5/3.5/BZ6/4.5/BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		19%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		81%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.83	0.6	51	39	31	25	49	38	30	25	45	35	28	24	41	33	27	23	19	
	中	0.81	0.8	61	49	41	35	58	47	39	34	53	44	37	32	48	41	35	31	27	
	否	0.77	1.0	67	56	48	41	64	54	46	40	59	50	43	38	54	46	41	36	32	
			1.25	73	63	55	49	70	60	53	47	64	56	50	45	59	52	47	43	38	
下方投影面積			1.5	77	68	60	54	74	65	58	53	68	61	55	50	62	56	51	47	42	
			2.0	83	75	68	63	80	72	66	61	73	67	62	58	67	62	58	54	48	
取付高さ	器具間隔最大限		2.5	87	80	74	68	83	77	71	67	77	71	67	63	71	66	63	59	53	
	横方向 (A)	縦方向 (B)	3.0	89	83	78	73	86	80	75	71	79	75	71	67	73	69	66	63	56	
1.5m	2.02m	2.08m	4.0	93	88	83	79	89	85	80	77	83	79	75	72	77	73	71	68	61	
2	2.67	2.65	5.0	95	90	87	83	91	87	84	81	85	82	79	76	79	76	74	71	64	
2.5	3.31	3.23	7.0	97	94	91	88	94	91	88	85	87	85	83	80	81	79	77	76	68	
3	3.96	3.83	10.0	99	97	94	92	96	94	91	89	89	87	86	84	83	82	80	79	71	

