

屋内照明器具特性	
品番 (品名)	LGW50633U
光源	LDA7L-G/K6 x2 810.0 lm
管理番号	K0169056(0)DB1
BZ分類	BZ6

器具効率	53%	天井	80%				70%				50%				30%				0%																					
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																					
		床	10%				10%				10%				10%				0%																					
上方光束	8%	室指数																			照明率 (X0.01)																			ZCM
下方光束	45%																																							
保守率	良 中 否	0.63	0.6	0.6	0.6	0.6	2.7	2.0	1.6	1.3	2.6	1.9	1.5	1.2	2.3	1.8	1.4	1.2	2.2	1.7	1.4	1.1	1.0																	
		0.6	0.6	0.6	0.6	0.6	0.8	3.2	2.5	2.1	1.7	3.0	2.4	2.0	1.7	2.8	2.3	1.9	1.6	2.6	2.1	1.8	1.6	1.4																
		0.56	0.56	0.56	0.56	0.56	1.0	3.5	2.9	2.4	2.1	3.3	2.8	2.4	2.0	3.1	2.6	2.2	1.9	2.8	2.4	2.1	1.9	1.6																
		0.56	0.56	0.56	0.56	0.56	1.25	3.8	3.2	2.8	2.4	3.6	3.1	2.7	2.4	3.3	2.9	2.6	2.3	3.1	2.7	2.4	2.2	1.9																
下方投影面積	c m ²	1.5	1.5	1.5	1.5	4.0	3.5	3.1	2.7	3.9	3.4	3.0	2.7	3.5	3.1	2.8	2.5	3.3	2.9	2.6	2.4	2.1																		
		2.0	2.0	2.0	2.0	2.0	4.3	3.8	3.5	3.1	4.1	3.7	3.4	3.1	3.8	3.5	3.2	2.9	3.5	3.2	3.0	2.8	2.5																	
取付高さ	器具間隔最大限		H m	1.33 H m	1.33 H m	2.5	2.5	2.5	2.5	2.5	4.5	4.1	3.8	3.5	4.3	4.0	3.6	3.4	4.0	3.7	3.4	3.2	3.0	2.7																
	横方向 (A)	縦方向 (B)				3.0	3.0	3.0	3.0	3.0	3.0	3.0	4.7	4.3	4.0	3.7	4.5	4.1	3.9	3.6	4.2	3.9	3.6	3.4	3.2	2.9														
					4.0	4.0	4.0	4.0	4.0	4.0	4.8	4.5	4.3	4.0	4.7	4.4	4.1	3.9	4.3	4.1	3.9	3.7	4.0	3.9	3.7	3.5	3.2													
					5.0	5.0	5.0	5.0	5.0	5.0	4.7	4.5	4.2	4.8	4.5	4.3	4.1	4.5	4.3	4.1	3.9	4.2	4.0	3.9	3.7	3.5	3.4													
					7.0	7.0	7.0	7.0	7.0	5.1	4.9	4.7	4.5	4.9	4.7	4.6	4.4	4.6	4.5	4.3	4.2	4.3	4.2	4.1	4.0	3.9	3.7	3.6												
					10.0	10.0	10.0	10.0	10.0	5.2	5.1	4.9	4.8	5.0	4.9	4.8	4.6	4.7	4.6	4.5	4.4	4.4	4.3	4.3	4.2	4.1	4.0	3.9	3.8											

