

屋内照明器具特性

品番 (品名)	L G W 8 5 2 3 8 S															
光源	L L D 3 0 2 0 M L C B 1 × 1 7 1 5 . 0 l m															
管理番号	K 0 1 8 0 4 4 3 (0) D R 1															
B Z 分類	B Z 5															

器具効率	50 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	3 %	室指数	照明率 (X 0 . 0 1)																Z C M		
下方光束	47 %																				
保守率	良	0.63	0.6	2.7	2.1	1.7	1.4	2.6	2.1	1.7	1.4	2.5	2.0	1.6	1.4	2.3	1.9	1.6	1.4	1.2	
	中	0.6	0.8	3.2	2.6	2.2	1.9	3.1	2.5	2.2	1.9	2.9	2.4	2.1	1.8	2.7	2.3	2.0	1.8	1.6	
	否	0.56	1.0	3.5	2.9	2.5	2.2	3.4	2.9	2.5	2.2	3.2	2.8	2.4	2.2	3.0	2.6	2.3	2.1	2.0	
			1.25	3.8	3.3	2.9	2.6	3.7	3.2	2.8	2.6	3.5	3.1	2.7	2.5	3.3	2.9	2.7	2.4	2.3	
下方投影面積			1.5	4.0	3.5	3.2	2.9	3.9	3.4	3.1	2.8	3.7	3.3	3.0	2.7	3.5	3.1	2.9	2.7	2.5	
	等価発光面積		2.0	4.3	3.9	3.5	3.3	4.2	3.8	3.5	3.2	3.9	3.6	3.4	3.1	3.7	3.5	3.2	3.0	2.8	
取付高さ	器具間隔最大限		2.5	4.5	4.1	3.8	3.6	4.3	4.0	3.7	3.5	4.1	3.8	3.6	3.4	3.9	3.7	3.5	3.3	3.1	
	横方向 (A)	縦方向 (B)	3.0	4.6	4.3	4.0	3.8	4.5	4.2	3.9	3.7	4.3	4.0	3.8	3.6	4.0	3.8	3.7	3.5	3.3	
H m	1.20 H m	1.20 H m	4.0	4.8	4.5	4.3	4.1	4.6	4.4	4.2	4.0	4.4	4.2	4.0	3.9	4.2	4.1	3.9	3.8	3.5	
			5.0	4.9	4.7	4.5	4.3	4.8	4.6	4.4	4.2	4.5	4.4	4.2	4.1	4.3	4.2	4.1	3.9	3.7	
			7.0	5.0	4.8	4.7	4.5	4.9	4.7	4.6	4.5	4.7	4.5	4.4	4.3	4.5	4.4	4.3	4.2	3.9	
			10.0	5.1	5.0	4.9	4.7	5.0	4.9	4.8	4.7	4.8	4.7	4.6	4.5	4.6	4.5	4.4	4.3	4.1	

