

# 屋内照明器具特性

品番 (品名)	L G W 8 5 2 3 8 S														
光源	LLD40001CQ1 ×1                      845.0 l m														
管理番号	K0180445 ( 0 ) DR 1														
B Z 分類	B Z 5														

器具効率	52 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	5 %																			
下方光束	47 %																			
室指数	照明率 ( X 0.01 )                      Z C M																			
保守率	良 0.63 中 0.6 否 0.56	0.6	28	22	18	15	27	21	18	15	26	20	17	14	24	20	16	14	13	
		0.8	33	27	23	20	32	27	23	20	30	25	22	19	28	24	21	19	17	
		1.0	37	31	27	24	36	30	26	23	33	29	25	23	31	27	25	22	20	
		1.25	40	34	30	27	38	34	30	27	36	32	29	26	34	31	28	26	24	
下方投影面積	c m <sup>2</sup>	1.5	42	37	33	30	41	36	33	30	38	34	31	29	36	33	30	28	26	
		2.0	45	41	37	34	43	40	37	34	41	38	35	33	39	36	34	32	30	
取付高さ	器具間隔最大限		2.5	47	43	40	37	45	42	39	37	43	40	38	36	40	38	36	34	32
	横方向 ( A )	縦方向 ( B )	3.0	48	45	42	40	47	44	41	39	44	42	40	38	42	40	38	36	34
H m	1.25 H m	1.25 H m	4.0	50	47	45	43	48	46	44	42	46	44	42	40	43	42	40	39	37
			5.0	51	48	46	45	49	47	46	44	47	45	44	42	45	43	42	41	38
			7.0	52	50	49	47	51	49	48	46	48	47	46	45	46	45	44	43	40
			10.0	53	52	50	49	52	50	49	48	49	48	47	47	47	46	45	45	42

