

# 屋内照明器具特性

|         |                         |           |
|---------|-------------------------|-----------|
| 品番 (品名) | NNLK41517J + NNL4400ENP |           |
| 光源      | LED5000_85_3920 ×1      | 3920.0 lm |
| 管理番号    | K0130921 (7) DB 1       |           |
| BZ分類    | BZ5                     |           |

| 器具効率   | 100 %           | 天井      | 80 % |               |      |      | 70 % |      |      |     | 50 % |      |     |     | 30 % |      |     |     | 0 % |     |  |  |  |
|--------|-----------------|---------|------|---------------|------|------|------|------|------|-----|------|------|-----|-----|------|------|-----|-----|-----|-----|--|--|--|
|        |                 |         | 壁    | 70            | 50   | 30   | 10   | 70   | 50   | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50  | 30  |     | 10  |  |  |  |
| 上方光束   | 0 %             | 反射率     | 床    | 10 %          |      |      |      | 10 % |      |     |      | 10 % |     |     |      | 10 % |     |     |     | 0 % |  |  |  |
| 下方光束   | 100 %           |         | 室指数  | 照明率 ( X0.01 ) |      |      |      |      |      |     |      |      |     |     |      |      |     |     |     |     |  |  |  |
| 保守率    | 良               | 0.81    | 0.6  | 5.6           | 4.4  | 3.6  | 3.1  | 5.5  | 4.3  | 3.6 | 3.0  | 5.2  | 4.2 | 3.5 | 3.0  | 5.0  | 4.1 | 3.5 | 3.0 | 2.8 |  |  |  |
|        | 中               | 0.77    | 0.8  | 6.6           | 5.5  | 4.7  | 4.1  | 6.5  | 5.4  | 4.6 | 4.1  | 6.2  | 5.2 | 4.6 | 4.1  | 5.9  | 5.1 | 4.5 | 4.0 | 3.8 |  |  |  |
|        | 否               | 0.68    | 1.0  | 7.3           | 6.2  | 5.4  | 4.8  | 7.1  | 6.1  | 5.4 | 4.8  | 6.8  | 6.0 | 5.3 | 4.8  | 6.6  | 5.8 | 5.2 | 4.8 | 4.5 |  |  |  |
|        |                 |         | 1.25 | 7.9           | 6.9  | 6.2  | 5.6  | 7.7  | 6.8  | 6.1 | 5.6  | 7.4  | 6.6 | 6.0 | 5.5  | 7.1  | 6.5 | 5.9 | 5.5 | 5.3 |  |  |  |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5  | 8.3           | 7.4  | 6.7  | 6.2  | 8.1  | 7.3  | 6.7 | 6.1  | 7.8  | 7.1 | 6.6 | 6.1  | 7.6  | 6.9 | 6.5 | 6.0 | 5.8 |  |  |  |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0  | 8.9           | 8.1  | 7.5  | 7.0  | 8.7  | 8.0  | 7.5 | 7.0  | 8.4  | 7.8 | 7.3 | 6.9  | 8.1  | 7.6 | 7.2 | 6.8 | 6.6 |  |  |  |
| 取付高さ   | 器具間隔最大限         |         | 2.5  | 9.2           | 8.6  | 8.1  | 7.6  | 9.1  | 8.5  | 8.0 | 7.6  | 8.8  | 8.3 | 7.9 | 7.5  | 8.5  | 8.1 | 7.7 | 7.4 | 7.1 |  |  |  |
|        | 横方向 (A)         | 縦方向 (B) |      |               |      |      |      |      |      |     |      |      |     |     |      |      |     |     |     |     |  |  |  |
| 1.5m   | 1.97m           | 2.17m   | 3.0  | 9.5           | 8.9  | 8.5  | 8.1  | 9.3  | 8.8  | 8.4 | 8.0  | 9.0  | 8.6 | 8.2 | 7.9  | 8.8  | 8.4 | 8.1 | 7.8 | 7.5 |  |  |  |
| 2      | 2.6             | 2.74    | 4.0  | 9.8           | 9.4  | 9.0  | 8.7  | 9.7  | 9.3  | 8.9 | 8.6  | 9.4  | 9.0 | 8.7 | 8.5  | 9.1  | 8.8 | 8.6 | 8.3 | 8.1 |  |  |  |
| 2.5    | 3.23            | 3.33    | 5.0  | 10.0          | 9.7  | 9.3  | 9.0  | 9.9  | 9.5  | 9.2 | 9.0  | 9.6  | 9.3 | 9.1 | 8.8  | 9.3  | 9.1 | 8.9 | 8.7 | 8.4 |  |  |  |
| 3      | 3.86            | 3.93    | 7.0  | 10.2          | 10.0 | 9.7  | 9.5  | 10.1 | 9.8  | 9.6 | 9.4  | 9.8  | 9.6 | 9.4 | 9.2  | 9.6  | 9.4 | 9.2 | 9.1 | 8.8 |  |  |  |
|        |                 |         | 10.0 | 10.4          | 10.2 | 10.0 | 9.9  | 10.3 | 10.1 | 9.9 | 9.8  | 10.0 | 9.9 | 9.7 | 9.6  | 9.8  | 9.6 | 9.5 | 9.4 | 9.1 |  |  |  |

