

# 屋内照明器具特性

品番 (品名)	L G W 8 5 2 3 8 Y	
光源	LLD2000LCE1 ×1	531.0 lm
管理番号	K0180440(0)DR1	
BZ分類	BZ5	

器具効率	56%	天井	80%				70%				50%				30%				0%		
	上方光束 5%		下方光束 51%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	31	24	19	16	30	23	19	16	28	22	18	16	26	21	18	15	14	
	中	0.6	0.8	36	29	25	22	35	29	25	21	33	28	24	21	31	26	23	20	19	
	否	0.56	1.0	40	34	29	26	38	33	29	25	36	31	28	25	34	30	27	24	22	
				1.25	43	37	33	30	42	36	32	29	39	35	31	29	37	33	30	28	26
下方投影面積	c m <sup>2</sup>		1.5	45	40	36	33	44	39	35	32	41	37	34	31	39	36	33	30	28	
	等価発光面積		c m <sup>2</sup>	2.0	48	44	40	37	47	43	40	37	44	41	38	36	42	39	37	35	32
取付高さ	器具間隔最大限		2.5	50	47	43	40	49	45	42	40	46	43	41	39	44	41	39	37	35	
	横方向 (A)	縦方向 (B)	3.0	52	48	45	43	50	47	45	42	48	45	43	41	45	43	41	39	37	
H m	1.25 H m	1.24 H m	4.0	54	51	48	46	52	50	47	45	50	47	46	44	47	45	44	42	40	
			5.0	55	52	50	48	53	51	49	47	51	49	47	46	48	47	45	44	41	
			7.0	56	54	53	51	55	53	52	50	52	51	50	48	50	49	48	47	44	
			10.0	57	56	55	53	56	55	53	52	53	52	51	50	51	50	49	48	46	

