

# 屋内照明器具特性

品番 (品名)	L G W 8 5 2 3 9 Y														
光源	LLD40001CQ1 ×1                      845.0 l m														
管理番号	K0180430 ( 1 ) DR 1														
B Z 分類	B Z 5														

器具効率	52 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	5 %	室指数	照明率 ( X 0.01 )																Z C M	
下方光束	47 %																			
保守率	良 中 否 0.63 0.6 0.56	0.6	2.9	2.2	1.8	1.5	2.8	2.2	1.8	1.5	2.6	2.1	1.7	1.5	2.4	2.0	1.7	1.4	1.3	
		0.8	3.4	2.7	2.3	2.0	3.2	2.7	2.3	2.0	3.0	2.6	2.2	2.0	2.9	2.4	2.1	1.9	1.8	
		1.0	3.7	3.1	2.7	2.4	3.6	3.0	2.7	2.4	3.4	2.9	2.6	2.3	3.2	2.8	2.5	2.3	2.1	
		1.25	4.0	3.5	3.1	2.8	3.9	3.4	3.0	2.7	3.6	3.2	2.9	2.7	3.4	3.1	2.8	2.6	2.4	
下方投影面積	c m <sup>2</sup>	1.5	4.2	3.7	3.4	3.1	4.1	3.6	3.3	3.0	3.8	3.5	3.2	2.9	3.6	3.3	3.1	2.8	2.6	
		2.0	4.5	4.1	3.8	3.5	4.4	4.0	3.7	3.4	4.1	3.8	3.5	3.3	3.9	3.6	3.4	3.2	3.0	
取付高さ	器具間隔最大限		2.5	4.7	4.3	4.0	3.8	4.5	4.2	3.9	3.7	4.3	4.0	3.8	3.6	4.1	3.8	3.6	3.5	3.2
	横方向 ( A )	縦方向 ( B )	3.0	4.8	4.5	4.2	4.0	4.7	4.4	4.1	3.9	4.4	4.2	4.0	3.8	4.2	4.0	3.8	3.7	3.4
H m	1.25 H m	1.25 H m	4.0	5.0	4.7	4.5	4.3	4.8	4.6	4.4	4.2	4.6	4.4	4.2	4.1	4.4	4.2	4.1	3.9	3.7
			5.0	5.1	4.9	4.7	4.5	4.9	4.8	4.6	4.4	4.7	4.5	4.4	4.3	4.5	4.3	4.2	4.1	3.8
			7.0	5.2	5.0	4.9	4.7	5.1	4.9	4.8	4.7	4.8	4.7	4.6	4.5	4.6	4.5	4.4	4.3	4.0
			10.0	5.3	5.2	5.1	4.9	5.2	5.1	5.0	4.9	4.9	4.8	4.8	4.7	4.7	4.6	4.6	4.5	4.2

