

屋内照明器具特性	
品番 (品名)	P M L E L 1 2 0 5 0 N C
光源	LED5000_70_3190 x1 3190.0 1 m
管理番号	K0177199 ( 0 ) D Y 1
B Z 分類	BZ2 / 0.9 / BZ3 / 6.0 / BZ4

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	5 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	95 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.69	0.6	66	56	50	45	65	55	49	45	62	54	49	45	60	53	48	44	42
	中	0.67	0.8	74	65	59	54	73	64	59	54	70	63	58	54	68	61	57	53	51
	否	0.63	1.0	80	72	65	61	78	71	65	60	75	69	64	60	72	67	62	59	57
			1.25	85	77	71	67	83	76	71	66	80	74	69	65	77	72	68	64	62
下方投影面積		cm <sup>2</sup>	1.5	88	81	76	71	86	80	75	71	83	78	73	70	80	75	72	68	66
等価発光面積		cm <sup>2</sup>	2.0	92	87	82	78	91	85	81	77	87	83	79	76	84	80	77	74	71
取付高さ	器具間隔最大限		2.5	95	90	86	82	93	89	85	81	90	86	83	80	86	83	81	78	75
	横方向 (A)	縦方向 (B)	3.0	97	93	89	85	95	91	88	85	92	88	85	83	88	86	83	81	77
1.5m	1.04 m	1.94 m	4.0	99	96	93	90	97	94	91	89	94	91	89	87	91	88	86	85	81
2	1.39	2.43	5.0	101	98	95	93	99	96	94	92	95	93	91	89	92	90	89	87	83
2.5	1.73	2.95	7.0	103	100	98	96	101	99	97	95	97	96	94	92	94	93	91	90	86
3	2.07	3.48	10.0	104	102	101	99	102	101	99	98	99	97	96	95	95	94	93	92	88

