

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XNN1067WA                  |
| 光源       | LED5000_85_850 ×1 850.0 lm |
| 管理番号     | K0176638 ( 0 ) DB 1        |
| BZ分類     | BZ1                        |

| 器具効率         |                 | 100 %           | 反射率  | 天井                | 80 % |     |     |     |     | 70 % |     |     |     |     | 50 % |     |    |    |    | 30 % |     |  |  |  | 0 % |
|--------------|-----------------|-----------------|------|-------------------|------|-----|-----|-----|-----|------|-----|-----|-----|-----|------|-----|----|----|----|------|-----|--|--|--|-----|
|              |                 |                 |      | 壁                 | 70   | 50  | 30  | 10  | 70  | 50   | 30  | 10  | 70  | 50  | 30   | 10  | 70 | 50 | 30 | 10   | 0 % |  |  |  |     |
|              |                 |                 |      | 床                 | 10 % |     |     |     |     | 10 % |     |     |     |     | 10 % |     |    |    |    | 10 % |     |  |  |  | 0 % |
| 上方光束<br>下方光束 |                 | 100 %           | 室指数  | 照明率 ( X0.01 ) ZCM |      |     |     |     |     |      |     |     |     |     |      |     |    |    |    |      |     |  |  |  |     |
| 保守率          |                 | 良<br>中<br>否     | 0.81 | 0.6               | 72   | 63  | 57  | 54  | 71  | 63   | 57  | 54  | 69  | 62  | 57   | 53  | 67 | 61 | 57 | 53   | 52  |  |  |  |     |
|              |                 |                 | 0.77 | 0.8               | 81   | 74  | 69  | 65  | 80  | 73   | 68  | 65  | 78  | 72  | 68   | 64  | 77 | 71 | 67 | 64   | 63  |  |  |  |     |
|              |                 |                 | 1.0  | 87                | 80   | 76  | 72  | 86  | 80  | 75   | 72  | 84  | 79  | 75  | 72   | 82  | 77 | 74 | 71 | 70   |     |  |  |  |     |
|              |                 |                 | 0.68 | 1.25              | 91   | 86  | 81  | 78  | 90  | 85   | 81  | 78  | 88  | 84  | 80   | 77  | 86 | 82 | 79 | 77   | 75  |  |  |  |     |
| 下方投影面積       |                 | cm <sup>2</sup> | 1.5  | 94                | 89   | 85  | 82  | 93  | 88  | 85   | 82  | 91  | 87  | 84  | 81   | 89  | 86 | 83 | 81 | 79   |     |  |  |  |     |
| 等価発光面積       |                 |                 | 2.0  | 98                | 94   | 90  | 88  | 97  | 93  | 90   | 87  | 94  | 91  | 89  | 86   | 92  | 90 | 88 | 86 | 84   |     |  |  |  |     |
| 取付<br>高さ     | 器具間隔最大限         |                 | 2.5  | 100               | 97   | 94  | 91  | 99  | 96  | 93   | 91  | 97  | 94  | 92  | 90   | 94  | 92 | 90 | 89 | 87   |     |  |  |  |     |
|              | 横方向 (A) 縦方向 (B) |                 | 3.0  | 101               | 98   | 96  | 94  | 100 | 97  | 95   | 93  | 98  | 96  | 94  | 92   | 96  | 94 | 92 | 91 | 89   |     |  |  |  |     |
| H m          | 1.25 H m        | 1.25 H m        | 4.0  | 103               | 101  | 99  | 97  | 102 | 100 | 98   | 96  | 100 | 98  | 96  | 95   | 98  | 96 | 95 | 94 | 91   |     |  |  |  |     |
|              |                 |                 | 5.0  | 104               | 102  | 101 | 99  | 103 | 101 | 100  | 98  | 101 | 99  | 98  | 97   | 99  | 97 | 96 | 95 | 93   |     |  |  |  |     |
|              |                 |                 | 7.0  | 105               | 104  | 103 | 101 | 104 | 103 | 102  | 101 | 102 | 101 | 100 | 99   | 100 | 99 | 98 | 97 | 95   |     |  |  |  |     |
|              |                 |                 | 10.0 | 106               | 105  | 104 | 103 | 105 | 104 | 103  | 102 | 103 | 102 | 101 | 101  | 100 | 99 | 99 | 99 | 96   |     |  |  |  |     |

