

# 屋内照明器具特性

品番 (品名)	XND9066WN	
光源	LED5000_80_9900 x1	9900.0lm
管理番号	K0179582(1)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 )																			ZCM
保守率	良 0.76	0.6	77	69	64	61	76	69	64	61	74	68	64	61	73	67	63	60	59	
	中 0.72		0.8	85	78	73	70	84	77	73	69	82	76	72	69	80	75	72	69	68
	否 0.64		1.0	89	83	79	75	88	82	78	75	86	81	78	75	84	80	77	74	73
下方投影面積	cm <sup>2</sup>	1.25	93	88	84	80	92	87	83	80	90	86	82	80	88	84	82	79	78	
		1.5	96	91	87	84	94	90	87	84	92	89	86	83	90	87	85	82	81	
等価発光面積	cm <sup>2</sup>	2.0	99	95	92	89	98	94	91	89	96	92	90	88	94	91	89	87	85	
		2.5	101	97	95	92	100	97	94	92	97	95	93	91	95	93	91	90	88	
取付高さ	器具間隔最大限		3.0	102	99	97	95	101	98	96	94	99	96	95	93	97	95	93	92	90
	横方向 (A)	縦方向 (B)	4.0	104	101	99	98	103	100	99	97	100	99	97	96	98	97	95	94	92
Hm	0.74Hm	0.74Hm	5.0	105	103	101	100	103	102	100	99	101	100	99	97	99	98	97	96	93
			7.0	106	104	103	102	105	103	102	101	102	101	100	99	100	99	99	98	95
			10.0	107	106	105	104	105	104	103	103	102	102	101	101	100	100	99	97	

