

# 屋内照明器具特性

|         |                    |          |
|---------|--------------------|----------|
| 品番 (品名) | XND9066WW          |          |
| 光源      | LED4000_80_9845 x1 | 9845.0lm |
| 管理番号    | K0179582(1)DB1     |          |
| BZ分類    | BZ1                |          |

|        |                 |         |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |
|--------|-----------------|---------|-----------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| 器具効率   | 100%            | 天井      | 80%             |      |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |    |
|        |                 |         | 70              | 50   | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |    |    |
| 上方光束   | 0%              | 反射率     | 壁               | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |    |
| 下方光束   | 100%            |         | 床               | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |    |
|        |                 | 室指数     | 照明率 (X0.01)     |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |    |
| 保守率    | 良               | 0.76    | 0.6             | 77   | 69  | 64  | 61  | 76  | 69  | 64  | 61  | 74  | 68  | 64  | 61  | 73  | 67  | 63  | 60  | 59 |    |
|        | 中               | 0.72    | 0.8             | 85   | 78  | 73  | 70  | 84  | 77  | 73  | 69  | 82  | 76  | 72  | 69  | 80  | 75  | 72  | 69  | 68 |    |
|        | 否               | 0.64    | 1.0             | 89   | 83  | 79  | 75  | 88  | 82  | 78  | 75  | 86  | 81  | 78  | 75  | 84  | 80  | 77  | 74  | 73 |    |
| 下方投影面積 | cm <sup>2</sup> | 等価発光面積  | cm <sup>2</sup> | 1.25 | 93  | 88  | 84  | 80  | 92  | 87  | 83  | 80  | 90  | 86  | 82  | 80  | 88  | 84  | 82  | 79 | 78 |
|        |                 |         |                 | 1.5  | 96  | 91  | 87  | 84  | 94  | 90  | 87  | 84  | 92  | 89  | 86  | 83  | 90  | 87  | 85  | 82 | 81 |
| 取付高さ   | 器具間隔最大限         |         | 2.5             | 101  | 97  | 95  | 92  | 100 | 97  | 94  | 92  | 97  | 95  | 93  | 91  | 95  | 93  | 91  | 90  | 88 |    |
|        | 横方向 (A)         | 縦方向 (B) | 3.0             | 102  | 99  | 97  | 95  | 101 | 98  | 96  | 94  | 99  | 96  | 95  | 93  | 97  | 95  | 93  | 92  | 90 |    |
| Hm     | 0.74Hm          | 0.74Hm  | 4.0             | 104  | 101 | 99  | 98  | 103 | 100 | 99  | 97  | 100 | 99  | 97  | 96  | 98  | 97  | 95  | 94  | 92 |    |
|        |                 |         | 5.0             | 105  | 103 | 101 | 100 | 103 | 102 | 100 | 99  | 101 | 100 | 99  | 97  | 99  | 98  | 97  | 96  | 93 |    |
|        |                 |         | 7.0             | 106  | 104 | 103 | 102 | 105 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 99  | 98  | 95 |    |
|        |                 |         | 10.0            | 107  | 106 | 105 | 104 | 105 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 100 | 99  | 97 |    |

