

屋内照明器具特性	
品番 (品名)	LGW5 1779 B
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0181598 (0) DR 1
BZ分類	BZ5/0.9/BZ4/6.0/BZ5/8.5/BZ4

器具効率	66 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	床		10 %				10 %				10 %				10 %				0 %
下方光束	66 %		室指数	照明率 (X0.01)																ZCM
保守率	良	0.63	0.6	3.8	3.0	2.5	2.1	3.7	3.0	2.5	2.1	3.5	2.9	2.4	2.1	3.4	2.8	2.4	2.1	2.0
	中	0.6	0.8	4.4	3.7	3.2	2.8	4.4	3.7	3.2	2.8	4.2	3.6	3.1	2.8	4.0	3.5	3.1	2.8	2.7
	否	0.56	1.0	4.9	4.2	3.7	3.3	4.8	4.1	3.7	3.3	4.6	4.0	3.6	3.3	4.4	3.9	3.6	3.3	3.1
			1.25	5.3	4.7	4.2	3.8	5.2	4.6	4.1	3.8	5.0	4.5	4.1	3.8	4.8	4.4	4.0	3.7	3.6
下方投影面積			1.5	5.5	5.0	4.5	4.2	5.4	4.9	4.5	4.2	5.2	4.8	4.4	4.1	5.1	4.7	4.4	4.1	3.9
			2.0	5.9	5.4	5.1	4.7	5.8	5.4	5.0	4.7	5.6	5.2	4.9	4.7	5.4	5.1	4.8	4.6	4.4
取付高さ	器具間隔最大限		2.5	6.1	5.7	5.4	5.1	6.0	5.7	5.3	5.1	5.8	5.5	5.2	5.0	5.7	5.4	5.2	4.9	4.8
	横方向 (A)	縦方向 (B)	3.0	6.3	5.9	5.6	5.4	6.2	5.9	5.6	5.3	6.0	5.7	5.5	5.3	5.8	5.6	5.4	5.2	5.0
H _m	1.22H _m	1.22H _m	4.0	6.5	6.2	6.0	5.8	6.4	6.1	5.9	5.7	6.2	6.0	5.8	5.6	6.0	5.9	5.7	5.5	5.4
			5.0	6.6	6.4	6.2	6.0	6.5	6.3	6.1	5.9	6.3	6.2	6.0	5.9	6.2	6.0	5.9	5.8	5.6
			7.0	6.8	6.6	6.4	6.3	6.7	6.5	6.4	6.2	6.5	6.4	6.2	6.1	6.3	6.2	6.1	6.0	5.8
			10.0	6.9	6.7	6.6	6.5	6.8	6.7	6.6	6.5	6.6	6.5	6.4	6.3	6.5	6.4	6.3	6.2	6.0

