

屋内照明器具特性

品番 (品名)	L G W 5 1 7 7 9 B									
光源	LLD4000LCB1 ×1					845.0 1 m				
管理番号	K0182053 (0) DR 1									
B Z 分類	B Z 5 / 0.9 / B Z 4 / 6.0 / B Z 5 / 8.5 / B Z 4									

器具効率	56 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
下方光束 56 %	室指数	照明率 (X 0.01)																Z C M			
保守率	良 0.63	0.6	3.2	2.5	2.1	1.8	3.1	2.5	2.1	1.8	3.0	2.4	2.1	1.8	2.9	2.4	2.0	1.8	1.7		
	中 0.6	0.8	3.8	3.1	2.7	2.4	3.7	3.1	2.7	2.4	3.5	3.0	2.6	2.4	3.4	2.9	2.6	2.3	2.2		
	否 0.56	1.0	4.1	3.5	3.1	2.8	4.0	3.5	3.1	2.8	3.9	3.4	3.0	2.8	3.7	3.3	3.0	2.8	2.6		
	下方投影面積	$c m^2$	1.25	4.4	3.9	3.5	3.2	4.4	3.9	3.5	3.2	4.2	3.8	3.4	3.2	4.0	3.7	3.4	3.2	3.0	
等価発光面積	$c m^2$	1.5	4.7	4.2	3.8	3.5	4.6	4.1	3.8	3.5	4.4	4.0	3.7	3.5	4.3	3.9	3.7	3.4	3.3		
	2.0	5.0	4.6	4.3	4.0	4.9	4.5	4.2	4.0	4.7	4.4	4.1	3.9	4.6	4.3	4.1	3.9	3.7			
取付高さ	器具間隔最大限		2.5	5.2	4.8	4.5	4.3	5.1	4.8	4.5	4.3	4.9	4.7	4.4	4.2	4.8	4.5	4.3	4.2	4.0	
	横方向 (A)	縦方向 (B)	3.0	5.3	5.0	4.8	4.5	5.2	5.0	4.7	4.5	5.1	4.8	4.6	4.4	4.9	4.7	4.5	4.4	4.2	
H m	1.22 H m	1.22 H m	4.0	5.5	5.2	5.0	4.9	5.4	5.2	5.0	4.8	5.2	5.1	4.9	4.7	5.1	4.9	4.8	4.7	4.5	
			5.0	5.6	5.4	5.2	5.1	5.5	5.3	5.2	5.0	5.4	5.2	5.1	4.9	5.2	5.1	5.0	4.9	4.7	
			7.0	5.7	5.6	5.4	5.3	5.6	5.5	5.4	5.3	5.5	5.4	5.3	5.2	5.3	5.2	5.2	5.1	4.9	
			10.0	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.4	5.4	5.3	5.3	5.1	

