

屋内照明器具特性

品番 (品名)	L S P S 9 0 1									
光源	LLD40001CQ1 ×1					845.0 1 m				
管理番号	K0176343 (0) DR 1									
B Z 分類	BZ3 / 0.9 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2									

器具効率	58 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		58 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	37	31	28	25	37	31	27	25	36	31	27	25	35	30	27	25	24	
	中	0.6	0.8	43	38	34	32	43	38	34	32	41	37	34	31	40	36	33	31	30	
	否	0.56	1.0	47	42	39	36	46	42	39	36	45	41	38	36	44	40	38	36	35	
			1.25	50	46	43	40	50	46	43	40	48	45	42	40	47	44	42	40	39	
下方投影面積	c m ²		1.5	52	49	46	43	52	48	45	43	50	47	45	43	49	46	44	42	41	
	等価発光面積		c m ²	2.0	55	52	49	47	54	51	49	47	53	50	48	47	51	49	48	46	45
取付高さ	器具間隔最大限		2.5	56	54	52	50	56	53	51	50	54	52	51	49	53	51	50	48	47	
	横方向 (A)	縦方向 (B)	3.0	58	55	53	52	57	55	53	51	55	54	52	51	54	53	51	50	49	
H m	1.17 H m	1.17 H m	4.0	59	57	56	54	58	57	55	54	57	55	54	53	55	54	53	52	51	
			5.0	60	58	57	56	59	58	56	55	57	56	55	54	56	55	54	54	52	
			7.0	60	59	58	58	60	59	58	57	58	58	57	56	57	56	56	55	54	
			10.0	61	60	60	59	60	60	59	58	59	58	58	57	58	57	57	56	55	

