

屋内照明器具特性	
品番 (品名)	LSPSC100L
光源	LLD2000MLCB1 ×1 531.0 lm
管理番号	K0176342(0)DR1
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2

器具効率	62%	天井	80%				70%				50%				30%				0%																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
		床	10%				10%				10%				10%				0%																																							
上方光束	0%	室指数																			照明率 (X0.01)																			ZCM																		
下方光束	62%																																																									
保守率	良 0.63 中 0.6 否 0.56	0.6	40	34	30	27	39	33	29	27	38	33	29	27	37	32	29	27	25																																							
		0.8	47	41	37	34	46	40	37	34	44	40	36	34	43	39	36	34	32																																							
		1.0	51	45	42	39	50	45	41	39	48	44	41	39	47	43	41	38	37																																							
		1.25	54	49	46	43	53	49	46	43	52	48	45	43	50	47	45	43	41																																							
下方投影面積	c m ²	1.5	56	52	49	46	55	51	49	46	54	50	48	46	52	50	47	45	44																																							
		2.0	59	56	53	51	58	55	53	50	56	54	52	50	55	53	51	49	48																																							
取付高さ	器具間隔最大限		2.5	61	58	55	53	60	57	55	53	58	56	54	53	57	55	53	51																																							
	横方向 (A)	縦方向 (B)	3.0	62	59	57	55	61	59	57	55	59	57	56	54	58	56	55	54	52																																						
H m	1.17H m	1.17H m	4.0	63	61	60	58	62	61	59	58	61	59	58	57	59	58	57	56	55																																						
			5.0	64	62	61	60	63	62	60	59	62	60	59	58	60	59	58	58	56	56																																					
			7.0	65	64	63	62	64	63	62	61	63	62	61	60	61	60	60	59	58																																						
			10.0	66	65	64	63	65	64	63	63	63	62	62	62	61	61	60	60	59																																						

