

# 屋内照明器具特性

品番 (品名)	NDN10800S				
光源	NNU140105KLE9 x1 1130.0 l m				
管理番号	K0160894 ( 0 ) DR 1				
BZ分類	BZ1 / 4.5 / BZ2 / 6.0 / BZ1				

器具効率	73 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		73 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.83	0.6	53	47	42	40	52	46	42	40	51	46	42	39	50	45	42	39	38	
	中	0.81	0.8	59	54	50	47	59	53	50	47	57	52	49	47	56	52	49	46	45	
	否	0.77	1.0	63	58	55	52	62	58	54	52	61	57	54	51	60	56	53	51	50	
			1.25	67	62	59	56	66	62	59	56	64	61	58	56	63	60	57	55	54	
下方投影面積	c m <sup>2</sup>		1.5	69	65	62	59	68	64	61	59	66	63	61	59	65	62	60	58	57	
	等価発光面積		c m <sup>2</sup>	2.0	71	68	66	63	71	68	65	63	69	66	64	63	67	65	63	62	60
取付高さ	器具間隔最大限		2.5	73	70	68	66	72	70	68	66	70	68	67	65	69	67	66	64	63	
	横方向 (A)	縦方向 (B)	3.0	74	72	70	68	73	71	69	68	72	70	68	67	70	69	67	66	64	
H m	1.19 H m	1.19 H m	4.0	75	74	72	71	75	73	71	70	73	72	70	69	71	70	69	68	66	
			5.0	76	75	73	72	75	74	73	72	74	73	72	71	72	71	70	70	68	
			7.0	77	76	75	74	76	75	74	74	75	74	73	72	73	72	72	71	69	
			10.0	78	77	76	76	77	76	76	75	75	75	74	74	74	73	73	72	70	

