

# 屋内照明器具特性

|         |                    |          |
|---------|--------------------|----------|
| 品番 (品名) | XND3568SV          |          |
| 光源      | LED3500_80_4000 x1 | 4000.0lm |
| 管理番号    | K0179569(0)DB1     |          |
| BZ分類    | BZ1                |          |

| 器具効率   | 100%            | 天井      | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|--------|-----------------|---------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
|        |                 |         | 70          | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  |     |    |
| 上方光束   | 0%              | 壁       | 10%         |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |
| 下方光束   | 100%            | 床       | 10%         |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |
|        |                 | 室指数     | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良               | 0.76    | 0.6         | 74  | 65  | 60  | 56  | 73  | 65  | 60  | 56  | 71  | 64  | 59  | 56  | 70  | 63  | 59  | 56  | 55 |
|        | 中               | 0.72    | 0.8         | 82  | 75  | 70  | 66  | 81  | 74  | 70  | 66  | 79  | 73  | 69  | 66  | 78  | 72  | 69  | 66  | 64 |
|        | 否               | 0.64    | 1.0         | 88  | 81  | 76  | 73  | 87  | 80  | 76  | 73  | 84  | 79  | 75  | 72  | 83  | 78  | 75  | 72  | 70 |
| 下方投影面積 | cm <sup>2</sup> | 1.25    | 92          | 86  | 82  | 78  | 91  | 85  | 81  | 78  | 89  | 84  | 81  | 78  | 87  | 83  | 80  | 77  | 76  |    |
|        |                 | 1.5     | 95          | 90  | 86  | 83  | 94  | 89  | 85  | 82  | 92  | 88  | 84  | 82  | 90  | 86  | 83  | 81  | 79  |    |
| 等価発光面積 | cm <sup>2</sup> | 2.0     | 98          | 94  | 91  | 88  | 97  | 93  | 90  | 88  | 95  | 92  | 89  | 87  | 93  | 90  | 88  | 86  | 84  |    |
|        |                 | 2.5     | 100         | 97  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93  | 91  | 89  | 87  |    |
| 取付高さ   | 器具間隔最大限         |         | 3.0         | 102 | 99  | 96  | 94  | 101 | 98  | 96  | 94  | 98  | 96  | 94  | 92  | 96  | 94  | 93  | 91  | 89 |
|        | 横方向 (A)         | 縦方向 (B) | 4.0         | 104 | 101 | 99  | 97  | 102 | 100 | 98  | 97  | 100 | 98  | 97  | 95  | 98  | 97  | 95  | 94  | 92 |
| Hm     | 0.74Hm          | 0.74Hm  | 5.0         | 105 | 103 | 101 | 99  | 103 | 102 | 100 | 99  | 101 | 100 | 98  | 97  | 99  | 98  | 97  | 96  | 93 |
|        |                 |         | 7.0         | 106 | 104 | 103 | 102 | 105 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 98  | 95 |
|        |                 |         | 10.0        | 107 | 106 | 105 | 104 | 105 | 104 | 104 | 103 | 103 | 102 | 102 | 101 | 101 | 100 | 100 | 99  | 97 |

