

屋内照明器具特性

品番 (品名)	NNN13600SK															
光源	LDA7L-G/D/S/K6 ×1 810.0 lm															
管理番号	K0179319(1)DB1															
BZ分類	BZ2/8.5/BZ1															

器具効率	24%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	0% 24%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.63 0.6 0.56	0.6	16	14	12	11	16	13	12	11	15	13	12	11	15	13	12	11	11		
		0.8	18	16	15	14	18	16	15	14	17	16	15	14	17	15	14	14	13		
		1.0	20	18	17	16	19	18	16	16	19	17	16	15	18	17	16	15	15		
		1.25	21	19	18	17	20	19	18	17	20	19	18	17	19	18	18	17	16		
下方投影面積 等価発光面積	c m ² c m ²	1.5	22	20	19	18	21	20	19	18	21	20	19	18	20	19	18	18	17		
		2.0	22	21	20	20	22	21	20	20	22	21	20	19	21	20	20	19	19		
		2.5	23	22	21	21	23	22	21	21	22	21	21	20	22	21	21	20	20		
取付高さ	器具間隔最大限		3.0	23	23	22	21	23	22	22	21	23	22	21	21	22	22	21	20		
	横方向 (A)	縦方向 (B)	4.0	24	23	23	22	24	23	23	22	23	23	22	22	23	22	22	21		
H m	1.01H m	1.39H m	5.0	24	24	23	23	24	23	23	23	23	23	23	22	23	23	22	22	21	
			7.0	24	24	24	23	24	24	24	23	24	23	23	23	23	23	23	23	22	22
			10.0	25	24	24	24	24	24	24	24	24	24	24	24	23	23	23	23	23	22

