

屋内照明器具特性

品番 (品名)	NNN13600SK									
光源	LDA7L-H/S/6 ×1					810.0 lm				
管理番号	K0178126(0)DB1									
BZ分類	BZ2/8.5/BZ1									

器具効率	38%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	38%																																																						
保守率	良 中 否 0.63 0.6 0.56	0.6	2.6	2.3	2.0	1.9	2.6	2.2	2.0	1.9	2.5	2.2	2.0	1.9	2.4	2.2	2.0	1.9	1.8																																				
		0.8	3.0	2.7	2.5	2.3	3.0	2.7	2.5	2.3	2.9	2.6	2.4	2.3	2.8	2.6	2.4	2.3	2.2																																				
		1.0	3.2	2.9	2.7	2.6	3.2	2.9	2.7	2.6	3.1	2.9	2.7	2.6	3.0	2.8	2.7	2.6	2.5																																				
		1.25	3.4	3.2	3.0	2.8	3.4	3.1	3.0	2.8	3.3	3.1	2.9	2.8	3.2	3.0	2.9	2.8	2.7																																				
下方投影面積	c m ²	1.5	3.5	3.3	3.1	3.0	3.5	3.3	3.1	3.0	3.4	3.2	3.1	3.0	3.3	3.2	3.1	2.9	2.9																																				
		2.0	3.7	3.5	3.4	3.2	3.6	3.5	3.3	3.2	3.5	3.4	3.3	3.2	3.5	3.3	3.3	3.2	3.1																																				
取付高さ	器具間隔最大限		2.5	3.8	3.6	3.5	3.4	3.7	3.6	3.5	3.4	3.6	3.5	3.4	3.3	3.6	3.5	3.4	3.2																																				
	横方向 (A)	縦方向 (B)	3.0	3.8	3.7	3.6	3.5	3.8	3.7	3.6	3.5	3.7	3.6	3.5	3.4	3.6	3.5	3.5	3.4																																				
H m	1.04 H m	1.32 H m	4.0	3.9	3.8	3.7	3.6	3.9	3.8	3.7	3.6	3.8	3.7	3.6	3.6	3.7	3.6	3.6	3.5																																				
			5.0	4.0	3.9	3.8	3.7	3.9	3.8	3.8	3.7	3.8	3.8	3.7	3.6	3.7	3.7	3.6	3.6	3.5																																			
			7.0	4.0	3.9	3.9	3.8	4.0	3.9	3.9	3.8	3.9	3.8	3.8	3.7	3.8	3.7	3.7	3.6																																				
			10.0	4.0	4.0	4.0	3.9	4.0	4.0	3.9	3.9	3.9	3.9	3.8	3.8	3.8	3.8	3.7	3.6																																				

