

# 屋内照明器具特性

|         |                    |           |
|---------|--------------------|-----------|
| 品番 (品名) | XND3 5 3 8 WV      |           |
| 光源      | LED3500_80_4050 ×1 | 4050.0 lm |
| 管理番号    | K0179574 (0) DB 1  |           |
| BZ分類    | BZ1                |           |

|        |         |                 |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |
|--------|---------|-----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率   | 100%    | 天井              | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |    |
|        | 上方光束    |                 | 0%            | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |
| 下方光束   | 100%    | 床               | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |
| 室指数    |         |                 | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |
| 保守率    | 良       | 0.76            | 0.6           | 74  | 66  | 60  | 56  | 73  | 65  | 60  | 56  | 71  | 64  | 60  | 56  | 70  | 64  | 59  | 56  | 55 |
|        | 中       | 0.72            | 0.8           | 82  | 75  | 70  | 66  | 81  | 74  | 70  | 66  | 79  | 73  | 69  | 66  | 78  | 72  | 69  | 66  | 64 |
|        | 否       | 0.64            | 1.0           | 87  | 81  | 76  | 73  | 86  | 80  | 76  | 72  | 84  | 79  | 75  | 72  | 82  | 78  | 74  | 72  | 70 |
| 下方投影面積 | 等価発光面積  | cm <sup>2</sup> | 1.25          | 92  | 86  | 82  | 78  | 91  | 85  | 81  | 78  | 88  | 84  | 80  | 77  | 87  | 83  | 80  | 77  | 75 |
|        |         |                 | 1.5           | 95  | 89  | 85  | 82  | 93  | 89  | 85  | 82  | 91  | 87  | 84  | 81  | 89  | 86  | 83  | 81  | 79 |
| 取付高さ   | 器具間隔最大限 |                 | 2.0           | 98  | 94  | 91  | 88  | 97  | 93  | 90  | 87  | 95  | 91  | 89  | 86  | 93  | 90  | 88  | 86  | 84 |
|        | 横方向 (A) | 縦方向 (B)         | 2.5           | 100 | 97  | 94  | 91  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 92  | 90  | 89  | 87 |
| Hm     | 0.73Hm  | 0.73Hm          | 3.0           | 102 | 99  | 96  | 94  | 100 | 98  | 95  | 93  | 98  | 96  | 94  | 92  | 96  | 94  | 92  | 91  | 89 |
|        |         |                 | 4.0           | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 95  | 98  | 96  | 95  | 94  | 91 |
|        |         |                 | 5.0           | 104 | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 98  | 96  | 95  | 93 |
|        |         |                 | 7.0           | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 97  | 95 |
|        |         |                 | 10.0          | 106 | 105 | 104 | 104 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 100 | 99  | 96 |

