

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | LSEBC5073         |          |
| 光源      | LED5000_70_765 x1 | 765.0 lm |
| 管理番号    | K0157034(0)D 1    |          |
| BZ分類    | BZ3               |          |

|        |                 |         |               |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |     |    |
|--------|-----------------|---------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|----|
| 器具効率   | 100%            | 天井      | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |    |    |    | 0%  |    |
|        |                 | 壁       | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束   | 0%              | 床       | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    | 0%  |    |
| 下方光束   | 100%            | 室指数     | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    | ZCM |    |
| 保守率    | 良               | 0.67    | 0.6           | 62  | 51  | 44  | 39  | 61  | 50  | 44  | 39  | 59  | 49  | 43  | 39  | 57 | 48 | 43 | 39  | 37 |
|        | 中               | 0.63    | 0.8           | 72  | 62  | 56  | 51  | 71  | 62  | 55  | 50  | 69  | 60  | 55  | 50  | 66 | 59 | 54 | 50  | 48 |
|        | 否               | 0.56    | 1.0           | 79  | 70  | 64  | 59  | 78  | 69  | 63  | 58  | 75  | 68  | 62  | 58  | 73 | 66 | 62 | 58  | 56 |
|        |                 |         | 1.25          | 85  | 77  | 71  | 66  | 83  | 76  | 70  | 66  | 81  | 74  | 69  | 65  | 78 | 73 | 69 | 65  | 63 |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5           | 89  | 81  | 76  | 71  | 87  | 81  | 75  | 71  | 84  | 79  | 74  | 71  | 82 | 77 | 73 | 70  | 68 |
|        | 等価発光面積          |         | 2.0           | 94  | 88  | 83  | 79  | 92  | 87  | 82  | 79  | 89  | 85  | 81  | 78  | 87 | 83 | 80 | 77  | 75 |
| 取付高さ   | 器具間隔最大限         |         | 2.5           | 96  | 92  | 87  | 84  | 95  | 91  | 87  | 83  | 92  | 89  | 85  | 82  | 90 | 87 | 84 | 81  | 79 |
|        | 横方向 (A)         | 縦方向 (B) | 3.0           | 98  | 94  | 91  | 87  | 97  | 93  | 90  | 87  | 95  | 91  | 88  | 86  | 92 | 89 | 87 | 85  | 82 |
| Hm     | 1.18Hm          | 1.22Hm  | 4.0           | 101 | 98  | 95  | 92  | 100 | 97  | 94  | 91  | 97  | 95  | 92  | 90  | 95 | 93 | 91 | 89  | 86 |
|        |                 |         | 5.0           | 102 | 100 | 97  | 95  | 101 | 99  | 96  | 94  | 99  | 97  | 95  | 93  | 96 | 95 | 93 | 91  | 89 |
|        |                 |         | 7.0           | 104 | 102 | 100 | 99  | 103 | 101 | 99  | 98  | 100 | 99  | 97  | 96  | 98 | 97 | 96 | 94  | 92 |
|        |                 |         | 10.0          | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99  | 99 | 99 | 98 | 97  | 94 |

