

屋内照明器具特性	
品番 (品名)	NNQ35921K
光源	LED5000_85_210 x1 210.0 l m
管理番号	K0180025 (1) DR 1
BZ分類	BZ9

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	36 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	64 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.77	0.6	4.4	3.1	2.3	1.7	4.1	2.9	2.1	1.6	3.5	2.5	1.8	1.4	2.9	2.1	1.6	1.2	7
	中	0.72	0.8	5.3	3.9	3.0	2.4	4.9	3.7	2.8	2.2	4.2	3.2	2.5	2.0	3.5	2.7	2.1	1.7	1.1
	否	0.68	1.0	5.9	4.6	3.7	3.0	5.4	4.3	3.4	2.8	4.6	3.7	3.0	2.5	3.9	3.2	2.6	2.1	1.5
			1.25	6.4	5.2	4.3	3.6	6.0	4.9	4.0	3.4	5.1	4.2	3.5	3.0	4.3	3.6	3.0	2.6	1.8
下方投影面積		cm ²	1.5	6.9	5.7	4.8	4.1	6.4	5.4	4.5	3.9	5.5	4.6	4.0	3.4	4.6	4.0	3.4	3.0	2.2
等価発光面積		cm ²	2.0	7.4	6.4	5.6	5.0	6.9	6.0	5.3	4.7	6.0	5.3	4.7	4.1	5.1	4.5	4.0	3.6	2.7
取付高さ	器具間隔最大限		2.5	7.8	7.0	6.2	5.6	7.3	6.5	5.8	5.3	6.3	5.7	5.1	4.7	5.4	4.9	4.5	4.1	3.1
	横方向 (A)	縦方向 (B)	3.0	8.1	7.3	6.6	6.0	7.6	6.9	6.3	5.7	6.6	6.0	5.5	5.1	5.7	5.2	4.8	4.4	3.4
1.5m	0	1.91m	4.0	8.5	7.8	7.2	6.7	8.0	7.4	6.8	6.3	7.0	6.5	6.0	5.6	6.0	5.6	5.3	5.0	3.9
2	0	2.52	5.0	8.8	8.2	7.6	7.2	8.2	7.7	7.2	6.8	7.2	6.8	6.4	6.0	6.3	5.9	5.6	5.3	4.2
2.5	0	3.15	7.0	9.1	8.6	8.2	7.8	8.5	8.1	7.7	7.4	7.5	7.2	6.9	6.6	6.6	6.3	6.0	5.8	4.6
3	0	3.77	10.0	9.3	8.9	8.6	8.3	8.8	8.5	8.2	7.9	7.8	7.5	7.3	7.0	6.8	6.6	6.4	6.2	5.0

