

# 屋内照明器具特性

品番 (品名)	NNN13513															
光源	LED3000_70_1265 x1 1265.0 1m															
管理番号	K0180978(2)DR1															
BZ分類	BZ7/0.7/BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束 下方光束	43% 57%	室指数	照明率 ( X0.01) ZCM																	
保守率	良 中 否 0.63 0.6 0.56	0.6	48	35	28	22	44	33	26	21	37	29	23	18	31	24	20	16	11	
		0.8	56	44	36	30	52	41	34	29	44	36	30	25	37	31	26	22	16	
		1.0	62	51	43	37	58	47	40	34	49	41	35	30	41	35	30	26	19	
		1.25	68	57	49	43	63	53	46	41	54	46	40	36	45	39	35	31	23	
下方投影面積 等価発光面積	c m <sup>2</sup>	1.5	72	62	54	48	67	58	51	45	57	50	45	40	48	43	38	35	26	
		2.0	77	69	62	56	72	64	58	53	62	56	51	47	52	48	44	40	30	
取付 高さ	器具間隔最大限		2.5	81	73	67	62	75	69	63	58	65	60	55	51	55	51	47	44	34
	横方向 (A)	縦方向 (B)	3.0	83	77	71	66	78	72	67	62	67	62	58	55	57	53	50	47	36
1.5m	1.96m	1.91m	4.0	87	81	76	72	81	76	72	68	70	66	63	60	60	57	54	52	40
2	2.61	2.51	5.0	89	84	80	76	83	79	75	72	72	69	66	63	62	59	57	55	42
2.5	3.27	3.12	7.0	91	88	84	81	86	82	79	77	75	72	70	67	64	62	60	59	45
3	3.9	3.73	10.0	93	91	88	86	88	85	83	81	76	75	73	71	66	64	63	62	48

