

# 屋内照明器具特性

品番 (品名)	LGB81873															
光源	LED3500_70_2425 x1 2425.0 lm															
管理番号	K0153988(0)DB1															
BZ分類	BZ8/0.7/BZ7															

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	32%	室指数	照明率 ( X0.01 )																ZCM		
下方光束	68%																				
保守率	良 中 否	0.67	0.6	47	34	26	20	44	32	25	19	38	29	22	17	33	25	20	16	12	
		0.63	0.8	56	43	34	28	52	41	33	27	46	36	29	24	39	32	26	22	17	
			1.0	62	50	41	34	58	47	39	33	51	42	35	30	44	37	31	27	21	
		0.56	1.25	67	56	47	41	63	53	45	39	55	47	40	35	48	41	36	32	25	
下方投影面積	c m <sup>2</sup>	1.5	72	61	53	46	67	58	50	44	59	51	45	40	51	45	40	36	28		
		2.0	77	68	60	54	73	64	57	52	64	57	51	47	56	50	46	42	33		
取付高さ	器具間隔最大限		2.5	81	73	66	60	76	69	62	57	67	61	56	52	59	54	50	46	37	
	横方向 (A)	縦方向 (B)	3.0	84	76	70	64	79	72	66	61	70	65	60	56	61	57	53	50	40	
1.5m	2.06m	2.15m	4.0	87	81	76	71	83	77	72	67	73	69	65	61	65	61	58	55	45	
2	2.72	2.71	5.0	90	84	80	75	85	80	76	72	76	72	68	65	67	64	61	58	48	
2.5	3.38	3.3	7.0	92	88	84	81	88	84	80	77	78	75	73	70	70	67	65	63	52	
3	4.04	3.89	10.0	95	92	88	86	90	87	84	82	81	78	76	74	72	70	68	67	55	

