

屋内照明器具特性

品番 (品名)	XND5 5 6 9 S W																
光源	LED4000_80_5445 x1 5445.0 lm																
管理番号	K0179658 (2) DB 1																
BZ分類	BZ2 / 0.7 / BZ1																

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01) ZCM																	
保守率	良 中 否	0.76	0.6	71	62	57	53	70	62	57	53	69	61	56	53	67	60	56	52	51
		0.72	0.8	81	73	67	64	80	72	67	63	78	71	67	63	76	70	66	63	61
			1.0	86	79	74	71	85	79	74	71	83	78	73	70	81	76	73	70	68
		0.64	1.25	91	85	80	77	90	84	80	77	88	83	79	76	86	82	78	76	74
下方投影面積	c m ²	1.5	94	89	84	81	93	88	84	81	91	86	83	80	88	85	82	80	78	
		2.0	98	93	90	87	97	93	89	87	94	91	88	86	92	89	87	85	83	
取付高さ	器具間隔最大限		2.5	100	96	93	91	99	95	93	90	96	94	91	89	94	92	90	88	86
	横方向 (A)	縦方向 (B)	3.0	101	98	96	93	100	97	95	93	98	96	93	92	96	94	92	90	88
H m	1.30 H m	1.30 H m	4.0	103	101	99	97	102	100	98	96	100	98	96	95	98	96	95	93	91
			5.0	104	102	101	99	103	101	100	98	101	99	98	97	99	97	96	95	93
			7.0	105	104	103	101	104	103	102	101	102	101	100	99	100	99	98	97	95
			10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	96	96

